

Material Data Safety Sheet

Emergency Telephone Numbers: 800-528-0997; 813-523-8053

REVIEW/UPDATE: 03/15/2005 BY: Mario Garneau

SECTION ONE - PRODUCT DESCRIPTION

NAME:	SEA HAWK CLEARGEAR 1400 Series
CHEMICAL DESCRIPTION:	ANTIFOULANT PAINT
FORMULA:	1400 SERIES WHITE, BLACK, GRAY

SECTION TWO - HAZARDOUS INGREDIENTS

______ ====

								CA	RCINOGE	N Y/N	
CHEMICAL	%	CAS NO.	TLV	PEL	SARA 302	SARA 313	CERCLA RQ#	NTP	IARC	OSHA	NOTE
TIN METHACRYLATE	15.6%	2155- 70-6	.1MG/M3	.1MG/M3	N	N	N	N	N	N	(1)
XYLENE	35.3%	1330- 20-7	100ppm	100ppm	N	Y	Y	N	N	N	(1)

APPEARANCE and Odor:	Liquid Solvent	BOILING POINT:	308º F
VAPOR PRESSURE:	(at 77º F) : 3@ 77 ºF	VAPOR DENSITY	(Air = 1); Heavier than air
SPECIFIC GRAVITY	(Water .1) : 1.5	VOTILE BY WEIGHT:	35.3%
SOLUBILITY IN WATER:	None	EVAPORATION RATE:	(Water = 1) Slower than ethe

SECTION		CIDE		EVDI	
SECTION	FUUR -		AIND		DAIA

	===========
FLASH POINT (°F / °C) [CLOSED CUP} :	79º F
FLAMMABLE LIMIT:	-LEL 1.1
	-UEL 6.6

EXTINQUISHER MEDIA: Carbon Dioxide Water Fog

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighter must wear self contained breathing apparatus or air masks. Containers exposed to fire should be kept cool with water vapor. UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION FIVE - HEALTH HAZARD DATA	

=======================================				
THRESHOLD LIMIT VALUE: See Section Two				
EFFECTS OF OVEREXPOSURE				
Inhalation:	Vapor or mist can cause headache, nausea, irritation to the nose, throat and lungs.			
Skin Contact:	Irritating upon repeated and prolonged contact.			
Eye Contact:	Slightly Irritating			
EMERGENCY & FIRST AID PRO	DCEDŪRES:			
Inhalation:	Move subject to fresh air.			
Eye/skin Contact:	Flush eyes with large amounts of water for at least 15 minutes . see physician if irritation			
	persists Wash affected skin area with soap and water.			



CALIFORNIA PROPOSITION 65 CHEMICALS: NONE

TSCA CERTIFICATION: All Chemicals in this product are listed, or exempt from listing, on the TSCA Inventory.

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using the material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are\ the only hazards which exist. Further the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third parties caused by this material. User assumes all risks associated with the use of this material.

(1) Abbreviations: N/E . Not Estabilshed, Supp. Conf. . Supplier Confidential, N/A . Not Applicable, ppm . Parts Per Million, mg/m3 . Milligrams per cubic meter, N- NO, Y . YES.