

**PREMIUM YACHT FINISHES**

14805 49th Street North • Clearwater, FL 33762
1-800-528-0997 U.S.A. only • (727) 523-8053

TIN BOOSTER

EMERGENCY TELEPHONE NUMBERS:

CHEMTREC: 800 424 9300
727 523 8053

UPDATE: 04/9/2004

BY: Clyde Garver

SECTION ONE: PRODUCT DESCRIPTION

NAME: TIN BOOSTER 1000T
CHEMICAL DESCRIPTION: Tin Methacrylate
FORMULA:

SECTION TWO – HAZARDOUS INGREDIENTS

CHEMICAL	%	CAS NO.	TLV	PEL	SA RA 302	SARA 313	CERCLA RQ#	CARCINOGEN Y/N			NOTE
								NTP	IARC	OSHA	
Xylene	55.0%	1330-20-7	100ppm	100ppm	N	Y	Y	N	N	N	(1)
Tributyltin Methacrylate	45.0 %	2155-70-6	0.1mg/m3	0.1mg/m3	N	N	N	N	N	N	(1)

SECTION THREE: - PHYSICAL DATA

APPEARANCE and ODOR: Liquid-Solvent
VAPOR PRESSURE: (mm of Hg.) 3@77°
SPECIFIC GRAVITY (Water =1) 1.50
SOLUBILITY IN WATER: None

BOILING POINT: 308°F
VAPOR DENSITY: Heavier than air
VOTILE BY WEIGHT: 55%
EVAPORATION RATE: Slower than air

SECTION FOUR – FIRE AND EXPLOSION DATA

FLASH POINT (°F / °C) [CLOSED CUP] : 79°F

FLAMMABLE LIMIT: -LEL 1.1
-UEL 6.6

EXTINGUISHER MEDIA: Carbon Dioxide, Water Fog

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighter must wear self-contained breathing apparatus or air masks. Containers exposed to fire should be kept cool with water vapor.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION FIVE – HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section Two
EFFECTS OF OVEREXPOSURE

Eye Contact: Corneal injury/eye damage

Irritation persists. Wash affected skin area with soap and water.

STABILITY:	STABLE	YES
	UNSTABLE	NO

CONDITIONS TO AVOID UNCONTROLLED POLYMERIZATION: NA

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store below 100°F /38°C, and in accordance with NFPA Code. Keep away from sparks or flame while stored, during use and until all vapors have dissipated. Extinguish pilot lights and all other sources of ignition. Keep area well ventilated. Use respirator if engineering controls are not adequate to maintain mist, vapor or dust below applicable standards.

STEPS TO FOLLOW IF MATERIAL IS SPILLED OR RELEASED: Remove all sources of ignition. Ventilate area. Use inert absorbent to collect residue, place in proper container, and dispose of proper container, and dispose of properly. Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Test for ignitability to determine applicable EPA hazardous waste numbers. See Section Two.

WASTE DISPOSAL METHODS: Incinerate in approved facility in accordance with all applicable regulations. Do not incinerate closed container. Avoid discharge into natural waters.

RESPIRATORY PROTECTION: Wear Respirator (MSHA/NIOSH) suitable for concentration and types of contaminants.

VENTILATION: Local ☒ Other
 Mechanical ☒

OTHER PROTECTIVE EQUIPMENT: NONE

OTHER PRECAUTIONS: Keep away from children, pets, livestock, and foodstuffs Not recommended for interior use.

TSCA CERTIFICATION: All Chemicals in this product are listed, or exempt from listing, on the TSCA Inventory.

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using the material in combination with any other material or any other process is the responsibility of the user. All materials present-unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third parties caused by this material. User assumes all risks associated with the use of this material

(1) Abbreviations: N/E – Not Established, Supp. Conf. – Supplier Confidential, N/A – Not Applicable, ppm – Parts Per Million, mg/m³ – Milligrams per cubic meter, N- NO, Y – YES.