

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 04/02/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : C3 Fast Cure Catalyst

Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

New Nautical Coatings, Inc. Sea Hawk Premium Yacht Finishes 14805 49th Street North Clearwater, FL 33762 USA Only: 1-800-528-0997 International: (727) 523-8053

1.4. Emergency telephone number

Emergency number : 813-523-8053

: CHEMTREC 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute Tox. 4 (Oral) H302 Acute Tox. 4 (Dermal) H312 Acute Tox. 4 (Inhalation) H332 Skin Corr. 1B H314 Skin Sens. 1 H317 Muta. 2 H341 STOT RE 2 H373 Aquatic Acute 2 H401 Aquatic Chronic 2 H411

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS07





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction

H341 - Suspected of causing genetic defects

H373 - May cause damage to organs through prolonged or repeated exposure

H401 - Toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P260 - Do not breathe dust, fume, mist, spray, vapours, gas P261 - Avoid breathing vapours, fume, gas, spray, mist, dust P264 - Wash hands, forearms and face thoroughly after handling P270 - Do not eat, drink or smoke when using this product

P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P272 - Contaminated work clothing must not be allowed out of the workplace

P273 - Avoid release to the environment

P280 - Wear eye protection, protective gloves, protective clothing, face shield P301+P312 - If swallowed: Call a doctor, a poison center if you feel unwell P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P308+P313 - If exposed or concerned: Get medical advice/attention

04/03/2015 C3 Fast Cure Catalyst Page 1

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P310 - Immediately call a doctor, a poison center

P312 - Call a doctor, a poison center if you feel unwell P314 - Get medical advice/attention if you feel unwell

P321 - Specific treatment (see first aid instructions on this label)

P330 - Rinse mouth

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P363 - Wash contaminated clothing before reuse

P391 - Collect spillage P405 - Store locked up

P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous

waste

2.3. Other hazards

Other hazards not contributing to the classification

: None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Formaldehyde, polymer with N,N'-bis(2-aminoethyl)-1,2-ethanediamine and phenol	(CAS No) 32610-77-8	60 - 100
Triethylenetetramine	(CAS No) 112-24-3	7 - 13
Amines, polyethylenepoly-	(CAS No) 68131-73-7	7 - 13
1,2-Ethanediamine, N,N'-bis(2-aminoethyl)-, polymer with methyloxirane	(CAS No) 26950-63-0	7 - 13
Phenol	(CAS No) 108-95-2	1 - 5
Tetraethylenepentamine	(CAS No) 112-57-2	1 - 5
Diethylenetriamine	(CAS No) 111-40-0	0.1 - 1

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if breathing is affected. If breathing is difficult, supply oxygen.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. Get medical attention immediately.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact

lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison

control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Harmful if swallowed, in contact with skin or if inhaled. Causes severe skin burns and eye

damage. May cause an allergic skin reaction. Suspected of causing genetic defects. May cause

damage to organs through prolonged or repeated exposure.

Symptoms/injuries after inhalation : Harmful if inhalation

Symptoms/injuries after skin contact : May cause an allergic skin reaction. Causes severe skin burns and eye damage. Harmful in

contact with skin.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Harmful if swallowed.

Chronic symptoms : Suspected of causing genetic defects. May cause damage to organs through prolonged or

repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Alcohol-resistant foam. Sand.

04/03/2015 C3 Fast Cure Catalyst 2/8

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the substance or mixture

Fire hazard : No data available. Explosion hazard : No data available.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Do not dispose of fire-fighting water in the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air

respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place

in a suitable container for disposal in accordance with the waste regulations (see Section 13). Exclude sources of ignition and ventilate the area. Waste from this product may be hazardous

as defined under RCRA (40 CFR 261).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Containers of this material may be hazardous when emptied. Do not breathe mist,

spray.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight,

Heat sources. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Formaldehyde, polymer with N,N'-bis(2-aminoethyl)-1,2-ethanediamine and phenol (32610-77-8)			
Remark (ACGIH)	OELs not established		
Remark (OSHA)	OELs not established		
Triethylenetetramine (112-24-3)			
Remark (ACGIH)	OELs not established		
Remark (OSHA)	OELs not established		
Phenol (108-95-2)			
ACGIH TWA (ppm)	5 ppm		
OSHA PEL (TWA) (mg/m³)	19 mg/m³		
OSHA PEL (TWA) (ppm)	5 ppm		
Amines, polyethylenepoly- (68131-73-7)			
Remark (ACGIH)	OELs not established		
Remark (OSHA)	OELs not established		

04/03/2015 C3 Fast Cure Catalyst 3/8

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tetraethylenepentamine (112-57-2)		
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	
Diethylenetriamine (111-40-0)		
ACGIH TWA (ppm)	1 ppm	
OSHA PEL (TWA) (mg/m³)	4 mg/m³	
OSHA PEL (TWA) (ppm)	1 ppm	
1,2-Ethanediamine, N,N'-bis(2-aminoethyl)-, polymer with methyloxirane (26950-63-0)		
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	

8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust

ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate

ventilation, especially in confined areas.

Personal protective equipment : Gloves. Wear chemical goggles and face shield in combination. Wear chemically impervious apron over labcoat and full coverage clothing.







Hand protection

Log Kow

Viscosity, kinematic

Viscosity, dynamic

Explosive properties

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Be aware that the chemical may penetrate the gloves. Frequent changes are advisable. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection : Wear eye protection, including chemical splash goggles and a face shield when possibility

exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection : Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or

other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Amber.

Odor : No data available : No data available Odor Threshold No data available Relative evaporation rate (butylacetate=1) No data available Melting point : No data available Freezing point : No data available No data available Boiling point Flash point : > 132 °C (>270°F) Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) No data available Vapour pressure : No data available Relative vapour density at 20 °C : No data available Relative density : No data available Density 1.06 g/cm³ Solubility No data available Log Pow : No data available

04/03/2015 C3 Fast Cure Catalyst 4/8

: No data available

No data available

No data available

: No data available

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidising properties : No data available Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremely high or low temperatures. Direct sunlight.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

No data available.

exposure)
Aspiration hazard

Symptoms/injuries after inhalation

Symptoms/injuries after skin contact

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Harmful in contact with skin. Inhalation: Harmful if inhaled.

. iouto toriion,	
Triethylenetetramine (112-24-3)	
LD50 oral rat	2500 mg/kg
ATE CLP (dermal)	1100.000 mg/kg bodyweight
Phenol (108-95-2)	
LD50 oral rat	317 mg/kg
LD50 dermal rat	525 mg/kg
LD50 dermal rabbit	630 mg/kg
ATE CLP (oral)	100.000 mg/kg bodyweight
ATE CLP (dermal)	300.000 mg/kg bodyweight
ATE CLP (gases)	700.000 ppmv/4h
ATE CLP (vapours)	3.000 mg/l/4h
ATE CLP (dust,mist)	0.500 mg/l/4h
Tetraethylenepentamine (112-57-2)	
LD50 oral rat	2100 mg/kg
Diethylenetriamine (111-40-0)	
LD50 oral rat	1080 mg/kg
LC50 inhalation rat (mg/l)	70 mg/l/4h (vapor)
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Suspected of causing genetic defects.
Carcinogenicity	: Not classified
Phenol (108-95-2)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated	: May cause damage to organs through prolonged or repeated exposure.

04/03/2015 C3 Fast Cure Catalyst 5/8

May cause an allergic skin reaction. Causes severe skin burns and eye damage. Harmful in

: Not classified

: Harmful if inhaled.

contact with skin.

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after eye contact : Causes serious eye damage. Symptoms/injuries after ingestion : Harmful if swallowed.

Chronic symptoms : Suspected of causing genetic defects. May cause damage to organs through prolonged or

repeated exposure.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities.

No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the

product to be released into the environment.

: 8 - Class 8 - Corrosive material 49 CFR 173.136

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN2735 Polyamines, liquid, corrosive, n.o.s., 8, III

UN-No.(DOT) : 2735 DOT NA no. : UN2735

Proper Shipping Name (DOT) : Polyamines, liquid, corrosive, n.o.s.

Department of Transportation (DOT) Hazard

Classes

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger

DOT Quantity Limitations Passenger aircraft/rail :

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 52 - Stow "separated from" acids

Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

04/03/2015 C3 Fast Cure Catalyst 6/8

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

C3 Fast Cure Catalyst

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

Phenol	CAS #:	108-95-2	
Section 302 (EHS) TPQ		500/10,000	lb
Section 304 EHS RQ		1000	lb
CERCLA RQ		1000	lb
Section 313		Listed on US SARA Section 313	

15.2. International regulations

CANADA

No additional information available.

15.3. US State regulations

California Proposition 65

This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

Triethylenetetramine (112-24-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Phenol (108-95-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Tetraethylenepentamine (112-57-2)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List U.S. Pennsylvania RTK (Right to Know) List

Diethylenetriamine (111-40-0)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revision 1.0: New SDS Created

: 04/02/2015 Revision date Other information : Author: NMR.

NFPA health hazard : 3 - Short exposure could cause serious temporary or


residual injury even though prompt medical attention was

given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

: 3* Health : 0 Flammability : 0 Physical Personal Protection

04/03/2015 C3 Fast Cure Catalyst 7/8

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material.

04/03/2015 C3 Fast Cure Catalyst 8/8