

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/05/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Alumahawk
Product form : Mixture
Other means of identification : AH7033

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

New Nautical Coatings, Inc. Sea Hawk Premium Yacht Finishes 14805 49th Street North Clearwater, FL 33762 USA Only: 1-800-528-0997 International: (727) 523-8053

1.4. Emergency telephone number

Emergency number : 813-523-8053

: CHEMTREC 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3 H226 Acute Tox. 4 (Oral) H302 Eye Irrit. 2A H319 Skin Sens. 1 H317 Muta. 1B H340 Carc. 1A H350 Repr. 2 H361 STOT RE 2 H373 Asp. Tox. 1 H304 Aquatic Acute 2 H401 Aquatic Chronic 2 H411

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS02

GHS07





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H340 - May cause genetic defects

H350 - May cause cancer

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H401 - Toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment P241 - Use explosion-proof ventilating equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P260 - Do not breathe dust, fume, gas, mist, spray, vapours P261 - Avoid breathing dust, fume, gas, mist, spray, vapours P264 - Wash hands, forearms and face thoroughly after handling

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P270 - Do not eat, drink or smoke when using this product

P272 - Contaminated work clothing must not be allowed out of the workplace

P273 - Avoid release to the environment

P280 - Wear eye protection, protective gloves, protective clothing

P301+P310 - IF SWALLOWED: Immediately call a doctor, a poison center

P301+P312 - If swallowed: Call a doctor, a poison center if you feel unwell

P302+P352 - If on skin: Wash with plenty of soap and water
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P308+P313 - If exposed or concerned: Get medical advice/attention

P314 - Get medical advice/attention if you feel unwell

P321 - Specific treatment (see first aid instructions on this label)

P330 - Rinse mouth

P331 - Do NOT induce vomiting

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P337+P313 - If eye irritation persists: Get medical advice/attention

P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use alcohol resistant foam, sand, carbon dioxide (CO2) to extinguish

P391 - Collect spillage

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous

2.3. Other hazards

Other hazards not contributing to the classification

: None under normal conditions.

Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Methyl isobutyl ketone	(CAS No) 108-10-1	7 - 13
Methyl propyl ketone	(CAS No) 107-87-9	3 - 7
Solvent naphtha, petroleum, light aliphatic	(CAS No) 64742-89-8	3 - 7
Toluene	(CAS No) 108-88-3	1 - 5
1-Butanol	(CAS No) 71-36-3	1 - 5
Trizinc diphosphate	(CAS No) 7779-90-0	1 - 5
Isobutyl isobutyrate	(CAS No) 97-85-8	0.5 - 1.5
Ethylbenzene	(CAS No) 100-41-4	0.1 - 1
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	0.1 - 1
Oxirane, methyl-, polymer with oxirane, monobutyl ether	(CAS No) 9038-95-3	0.1 - 1
Silica: Crystalline, quartz	(CAS No) 14808-60-7	0.1 - 1
Cobalt neodecanoate	(CAS No) 27253-31-2	0.1 - 1
Naphthenic acids, cobalt salts	(CAS No) 61789-51-3	0.1 - 1
Naphtha, petroleum, hydrotreated heavy	(CAS No) 64742-48-9	0.1 - 1
Zirconium ethyl hexoate	(CAS No) 22464-99-9	0.1 - 1
Methyl ethyl ketoxime	(CAS No) 96-29-7	0.1 - 1
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omega[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-	(CAS No) 104810-47-1	0.1 - 1
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	(CAS No) 104810-48-2	0.1 - 1

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.

08/05/2015 Alumahawk 2/12 AH7033

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at

least 15 minutes. Get medical attention immediately.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact

lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison

control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Harmful if swallowed. May be fatal if swallowed and enters airways. May cause an allergic skin

reaction. Causes serious eye irritation. May cause genetic defects. May cause cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs (central nervous system). May cause damage to organs through prolonged or repeated

exposure.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Harmful if swallowed. May be fatal if swallowed and enters airways.

Chronic symptoms : May cause genetic defects. May cause cancer. Suspected of damaging fertility. Suspected of

damaging the unborn child. Causes damage to organs. May cause damage to organs through

prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Alcohol-resistant foam. Sand.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

Explosion hazard : Product is not explosive. Under fire conditions closed containers may rupture or explode.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Do not dispose of fire-fighting water in the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air

respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams. Scoop solid spill into closing containers or bags. Small quantities of liquid spill: take up

in non-combustible absorbent material and shovel into container for disposal.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place

in a suitable container for disposal in accordance with the waste regulations (see Section 13). Exclude sources of ignition and ventilate the area. Waste from this product may be hazardous

as defined under RCRA (40 CFR 261).

6.4. Reference to other sections

No additional information available

08/05/2015 Alumahawk 3/12

AH7033

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Containers of this material may be hazardous when emptied. . Do not breathe mist, spray.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Direct sunlight,

Heat sources. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methyl propyl ketone (107-87-9)			
ACGIH STEL (ppm)	150 ppm		
OSHA PEL (TWA) (mg/m³)	700 mg/m³		
OSHA PEL (TWA) (ppm)	200 ppm		
OSHA PEL (STEL) (mg/m³)	875 mg/m³ Vacated		
OSHA PEL (STEL) (ppm)	250 ppm Vacated		
Toluene (108-88-3)			
ACGIH TWA (ppm)	20 ppm		
Remark (ACGIH)	Visual impair; female repro;		
Ethylbenzene (100-41-4)			
ACGIH TWA (ppm)	20 ppm		
Remark (ACGIH)	upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment		
OSHA PEL (TWA) (mg/m³)	435 mg/m³		
OSHA PEL (TWA) (ppm)	100 ppm		
OSHA PEL (STEL) (mg/m³)	545 mg/m³		
OSHA PEL (STEL) (ppm)	125 ppm		
Xylenes (o-, m-, p- isomers) (1330-20-7)	·		
ACGIH TWA (ppm)	100 ppm		
ACGIH STEL (ppm)	150 ppm		
OSHA PEL (TWA) (mg/m³)	435 mg/m³		
OSHA PEL (TWA) (ppm)	100 ppm		
OSHA PEL (STEL) (mg/m³)	655 mg/m³		
OSHA PEL (STEL) (ppm) 150 ppm			
Oxirane, methyl-, polymer with oxirane, mon	obutyl ether (9038-95-3)		
Remark (ACGIH)	OELs not established		
Remark (OSHA)	OELs not established		
Silica: Crystalline, quartz (14808-60-7)			
ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable fraction)		
OSHA PEL (TWA) (mg/m³)	(30)/(%SiO2 + 2) total dust; (10)/(%SiO2 + 2) respirable fraction		
OSHA PEL (TWA) (ppm)	(250)/(%SiO2 + 5) respirable fraction		
Methyl isobutyl ketone (108-10-1)	·		
ACGIH TWA (ppm)	20 ppm		
ACGIH STEL (ppm)	75 ppm		
OSHA PEL (TWA) (mg/m³)	410 mg/m³		
OSHA PEL (TWA) (ppm)	100 ppm		
Cobalt neodecanoate (27253-31-2)			
Remark (ACGIH)	OELs not established		

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Cobalt neodecanoate (27253-31-2)				
Remark (OSHA)	OELs not established			
Naphthenic acids, cobalt salts (61789-5	1-3)			
Remark (ACGIH)	OELs not established			
Remark (OSHA)	OELs not established			
Naphtha, petroleum, hydrotreated heav	y (64742-48-9)			
Remark (ACGIH)	OELs not established			
Remark (OSHA)	OELs not established			
Zirconium ethyl hexoate (22464-99-9)				
Remark (ACGIH)	OELs not established			
Remark (OSHA)	OELs not established			
Methyl ethyl ketoxime (96-29-7)				
Remark (ACGIH)	OELs not established			
Remark (OSHA)	OELs not established			
Trizinc diphosphate (7779-90-0)				
Remark (ACGIH)	OELs not established			
Remark (OSHA)	OELs not established			
1-Butanol (71-36-3)				
ACGIH TWA (ppm)	20 ppm			
OSHA PEL (TWA) (mg/m³)	300 mg/m³			
OSHA PEL (TWA) (ppm)	100 ppm			
Solvent naphtha, petroleum, light alipha	atic (64742-89-8)			
Remark (ACGIH)	OELs not established			
Remark (OSHA)	OELs not established			
Isobutyl isobutyrate (97-85-8)				
Remark (ACGIH)	OELs not established			
Remark (OSHA)	OELs not established			
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2 oxopropyl]omega[3-[3-(2H-benzotriaz (104810-47-1)	2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-zol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-			
Remark (ACGIH)	GIH) OELs not established			
emark (OSHA) OELs not established				
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2 oxopropyl]omegahydroxy- (104810-4	2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-8-2)			
Remark (ACGIH)	OELs not established			
Remark (OSHA)	OELs not established			

8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.



AH7033







Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

08/05/2015 Alumahawk 5/12

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection

Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Color : Green.

Odor : No data available Odor Threshold No data available рΗ No data available Relative evaporation rate (butylacetate=1) : No data available : No data available Melting point Freezing point No data available Boiling point No data available Flash point : 16 °C (60.8 °F) Auto-ignition temperature No data available Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapour pressure : No data available Relative vapour density at 20 °C : No data available

Relative density : 1.38

Solubility : No data available Log Pow : No data available Log Kow : No data available Viscosity, kinematic No data available Viscosity, dynamic : No data available Explosive properties : No data available Oxidising properties . No data available **Explosive limits** : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremely high or low temperatures. Direct sunlight.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

Methyl propyl ketone (107-87-9)	
LD50 oral rat	1600 mg/kg

Safety Data Sheet
Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

T	<u> </u>		
Methyl propyl ketone (107-87-9)	Table 1		
LD50 dermal rat	6480 mg/kg		
LC50 inhalation rat (ppm)	2000 ppm/4h		
Toluene (108-88-3)			
LD50 oral rat	2600 mg/kg		
LD50 dermal rabbit	12000 mg/kg		
LC50 inhalation rat (mg/l)	12.5 mg/l/4h		
Ethylbenzene (100-41-4)			
LD50 oral rat	3500 mg/kg		
LD50 dermal rabbit	15400 mg/kg		
LC50 inhalation rat (mg/l)	17.2 mg/l/4h		
ATE CLP (gases)	4500.000 ppmv/4h		
ATE CLP (vapours)	11.000 mg/l/4h		
ATE CLP (dust,mist)	1.500 mg/l/4h		
Xylenes (o-, m-, p- isomers) (1330-20-7)			
LD50 oral rat	3500 mg/kg		
ATE CLP (dermal)	1100.000 mg/kg bodyweight		
ATE CLP (gases)	4500.000 ppmv/4h		
ATE CLP (vapours)	11.000 mg/l/4h		
ATE CLP (dust,mist)	1.500 mg/l/4h		
Oxirane, methyl-, polymer with oxirane, mor	obutyl ether (9038-95-3)		
LD50 oral rat	7460 mg/kg		
LD50 dermal rabbit	14100 μl/kg		
LC50 inhalation rat (mg/l)	0.147 mg/l/4h		
Silica: Crystalline, quartz (14808-60-7)			
LD50 oral rat	500 mg/kg		
Methyl isobutyl ketone (108-10-1)			
LD50 oral rat	2080 mg/kg		
LD50 dermal rabbit	3000 mg/kg		
ATE CLP (gases)	4500.000 ppmv/4h		
ATE CLP (vapours)	11.000 mg/l/4h		
ATE CLP (dust,mist)	1.500 mg/l/4h		
Trizinc diphosphate (7779-90-0)			
LD50 oral rat	> 5000 mg/kg		
Naphtha, petroleum, hydrotreated heavy (64			
LD50 oral rat	> 5000 mg/kg		
LD50 dermal rabbit	> 3160 mg/kg		
Methyl ethyl ketoxime (96-29-7) LD50 oral rat	020		
LD50 dermal rabbit	930 mg/kg		
	0.2 mg/kg		
LC50 inhalation rat (mg/l) 20 mg/l/4h			
1-Butanol (71-36-3)	1 "		
LD50 oral rat	700 mg/kg		
LD50 dermal rabbit	3402 mg/kg		
LC50 inhalation rat (ppm)	> 8000 ppm/4h		
ATE CLP (oral) 500.000 mg/kg bodyweight			
Solvent naphtha, petroleum, light aliphatic (64742-89-8)			
LD50 oral rat	5000 mg/kg mouse		
LD50 dermal rabbit	3000 mg/kg		
Isobutyl isobutyrate (97-85-8)			
LC50 inhalation rat (ppm)	5000 ppm 6 h		
Skin corrosion/irritation	: Not classified		
Serious eye damage/irritation	: Causes serious eye irritation.		
Respiratory or skin sensitisation	: May cause an allergic skin reaction.		
Germ cell mutagenicity	: May cause genetic defects.		
Carcinogenicity	: May cause cancer.		

Alumahawk AH7033 08/05/2015 7/12

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)			
IARC group	3 - Not classifiable		
Ethylbenzene (100-41-4)			
IARC group	2B - Possibly carcinogenic to humans		
Xylenes (o-, m-, p- isomers) (1330-20-7)			
IARC group	3 - Not classifiable		
Silica: Crystalline, quartz (14808-60-7)			
IARC group	1 - Carcinogenic to humans		
Methyl isobutyl ketone (108-10-1)			
IARC group	2B - Possibly carcinogenic to humans		
Naphthenic acids, cobalt salts (61789-51-3)			
IARC group	2B - Possibly carcinogenic to humans		
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.		
Specific target organ toxicity (single exposure)	: Causes damage to organs (central nervous system)		
	Management designs to a consequent through a color and a consequent design according		

Specific target organ toxicity (repeated

exposure)

: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion

: Harmful if swallowed. May be fatal if swallowed and enters airways.

Chronic symptoms : May cause genetic defects. May cause cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs. May cause damage to organs through

prolonged or repeated exposure.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations

Waste treatment methods

Do not discharge to public wastewater systems without permit of pollution control authorities.

No discharge to surface waters is allowed without an NPDES permit.

: Dispose in a safe manner in accordance with local/national regulations. Do not allow the

product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1263 Paint related material (including paint thinning, drying, removing, or reducing

compound), 3, II

AH7033

UN-No.(DOT) : 1263 DOT NA no. : UN1263

Proper Shipping Name (DOT) : Paint related material

including paint thinning, drying, removing, or reducing compound

Department of Transportation (DOT) Hazard

Classes

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

08/05/2015 Alumahawk 8/12

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Minor Danger

DOT Quantity Limitations Passenger aircraft/rail :

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Alumahawk

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

1-Butanol	CAS #:	71-36-3	
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Section 302 (EHS) TPQ	Ib		
Section 304 EHS RQ	lb		
CERCLA RQ		5000	lb
Section 313		Listed on US SARA Section 313	

Toluene	CAS #: 108-88-3	
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Section 302 (EHS) TPQ	Ib	
Section 304 EHS RQ	Ib	
CERCLA RQ	1000 lb	
Section 313	Listed on US SARA Section 313	

Methyl isobutyl ketone	CAS #: 108-10-1	
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Section 302 (EHS) TPQ		Ib
Section 304 EHS RQ		Ib
CERCLA RQ	5000	lb
Section 313	Listed on US SARA Section 313	

15.2. International regulations

CANADA

No additional information available.

15.3. US State regulations

California Proposition 65

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	
Ethylbenzene (100-41-4)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Silica: Crystalline, quar	tz (14808-60-7)	<u> </u>	<u> </u>	<u> </u>
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Methyl isobutyl ketone	(108-10-1)	<u> </u>		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	No	
Benzene (71-43-2)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	Yes	
Arsenic (7440-38-2)	•			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	No	
Nickel (7440-02-0)	l .	l	l	I
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
			1112112	

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List U.S. Pennsylvania RTK (Right to Know) List

Toluene (108-88-3)

- U.S. Massachusetts Right To Know List U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Ethylbenzene (100-41-4)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Xylenes (o-, m-, p- isomers) (1330-20-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Silica: Crystalline, quartz (14808-60-7)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

Methyl isobutyl ketone (108-10-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Naphthenic acids, cobalt salts (61789-51-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

1-Butanol (71-36-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Isobutyl isobutyrate (97-85-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

Benzene (71-43-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Arsenic (7440-38-2)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances

Nickel (7440-02-0)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances

Barium sulfate (7727-43-7)

- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List

Talc (14807-96-6)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revision 1.0: New SDS Created.

Revision date : 08/05/2015 Other information : Author: NMR.

NFPA health hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was


given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 3* Flammability : 3

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Physical : 0
Personal Protection :

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material.