

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 01/22/2015 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : C1 Extra Slow Catalyst

Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

New Nautical Coatings, Inc. Sea Hawk Premium Yacht Finishes 14805 49th Street North Clearwater, FL 33762 USA Only: 1-800-528-0997 International: (727) 523-8053

1.4. Emergency telephone numbers

Emergency number : CHEMTREC day or night inside USA & Canada

1-800-424-9300

: CHEMTREC day or night outside USA & Canada

+1-703-741-5970 Poison Control Center 1-800-222-1222

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute Tox. 4 (Oral) H302 Acute Tox. 4 (Inhalation) H332 Skin Corr. 1B H314 Skin Sens. 1 H317 Repr. 2 H361 STOT SE 3 H335 Aquatic Acute 1 H400 Aquatic Chronic 1 H410

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS07





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H302+H332 - Harmful if swallowed or if inhaled

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction H335 - May cause respiratory irritation

H361 - Suspected of damaging fertility. Suspected of damaging the unborn child

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P260 - Do not breathe dust, fume, mist, spray, vapours, gas P261 - Avoid breathing vapours, fume, gas, spray, mist, dust P264 - Wash hands, forearms and face thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P272 - Contaminated work clothing must not be allowed out of the workplace

P273 - Avoid release to the environment

P280 - Wear eye protection, protective gloves, protective clothing, face shield P301+P312 - If swallowed: Call a doctor, a poison center if you feel unwell P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

04/28/2015 C1 Extra Slow Catalyst Page 1

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Rinse skin with water/shower

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P308+P313 - If exposed or concerned: Get medical advice/attention

P310 - Immediately call a doctor, a poison center P312 - Call a doctor, a poison center if you feel unwell

P321 - Specific treatment (see first aid instructions on this label)

P330 - Rinse mouth

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P363 - Wash contaminated clothing before reuse

P391 - Collect spillage

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous

waste

2.3. Other hazards

Other hazards not contributing to the

classification

: None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
4-tert-Butylphenol	(CAS No) 98-54-4	10 - 30
Propylene glycol diamine, 2-amino-, diether with Propylene	(CAS No) 9046-10-0	10 - 30
1,3-Benzenedimethanamine	(CAS No) 1477-55-0	7 - 13
Trimethylhexamethylenediamine	(CAS No) 25620-58-0	3 - 7
Nonylphenols	(CAS No) 25154-52-3	1 - 5

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if breathing is affected. If breathing is difficult, supply oxygen.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at

least 15 minutes. Get medical attention immediately.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact

lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison

control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Harmful if swallowed or if inhaled. Causes severe skin burns and eye damage. May cause an

allergic skin reaction. May cause respiratory irritation. Suspected of damaging fertility.

Suspected of damaging the unborn child.

Symptoms/injuries after inhalation : Harmful if inhaled.

Symptoms/injuries after skin contact : May cause an allergic skin reaction. Causes severe skin burns and eye damage.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Harmful if swallowed.

Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Alcohol-resistant foam. Sand.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Must be preheated before ignition can occur.

04/28/2015 C1 Extra Slow Catalyst 2/1

Safety Data Sheet

Reactivity

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard

No data available.No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Do not dispose of fire-fighting water in the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air

respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place

in a suitable container for disposal in accordance with the waste regulations (see Section 13). Exclude sources of ignition and ventilate the area. Waste from this product may be hazardous

as defined under RCRA (40 CFR 261).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes. Keep away from heat, hot surfaces,

smoking and when leaving work. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Containers of this material may be hazardous when emptied. Do not breathe mist,

spray.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from: Direct sunlight,

Heat sources. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1,3-Benzenedimethanamine (1477-55-0)				
ACGIH Ceiling (mg/m³)	0.1 mg/m³			
OSHA PEL (Ceiling) (mg/m³)	0.1 mg/m³ Vacated			
Nonylphenols (25154-52-3)				
Remark (ACGIH)	OELs not established			
Remark (OSHA)	OELs not established			
Trimethylhexamethylenediamine (25620-58-0)				
Remark (ACGIH)	OELs not established			
Remark (OSHA)	OELs not established			
4-tert-Butylphenol (98-54-4)				
Remark (ACGIH)	OELs not established			
Remark (OSHA)	OELs not established			
Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)				
Remark (ACGIH)	OELs not established			

04/28/2015 C1 Extra Slow Catalyst 3/1

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)			
	Remark (OSHA)	OELs not established	

8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust

ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate

ventilation, especially in confined areas.

Personal protective equipment : Gloves. Wear chemical goggles and face shield in combination. Protective clothing.



Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could

occur. Be aware that the chemical may penetrate the gloves. Frequent changes are advisable. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove

supplier.

: 93.3 °C (200°F)

Eye protection : Wear eye protection, including chemical splash goggles and a face shield when possibility

exists for eye contact due to spraying liquid or airborne particles. Chemical goggles and face

shield must be worn in combination.

Skin and body protection : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection : Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or

other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Yellow.

Odor : No data available
Odor Threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available
Density : 0.96 g/cm³

Solubility : No data available Log Pow No data available No data available Log Kow : No data available Viscosity, kinematic Viscosity, dynamic : No data available Explosive properties : No data available Oxidising properties No data available Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flash point

No dangerous reactions known under normal conditions of use.

04/28/2015 C1 Extra Slow Catalyst 4/1

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremely high or low temperatures. Direct sunlight.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

No data available.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Inhalation: Harmful if inhaled

. Oral. Harmiui ii Swallowed. Ilmalation. Harmiui ii ilmaled.		
0)		
660 mg/kg		
2 g/kg		
700 ppm/1h		
580 mg/kg		
2031 mg/kg		
580.000 mg/kg bodyweight		
2031.000 mg/kg bodyweight		
Trimethylhexamethylenediamine (25620-58-0)		
910 mg/kg		
2990 mg/kg		
2318 mg/kg		
: Causes severe skin burns and eye damage.		
: Not classified		
: May cause an allergic skin reaction.		
: Not classified		
: Not classified		

: Suspected of damaging fertility. Suspected of damaging the unborn child. Reproductive toxicity

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

: Not classified Aspiration hazard Symptoms/injuries after inhalation : Harmful if inhaled.

Symptoms/injuries after skin contact : May cause an allergic skin reaction. Causes severe skin burns and eye damage.

Symptoms/injuries after eye contact : Causes serious eye damage. : Harmful if swallowed. Symptoms/injuries after ingestion

Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child.

SECTION 12: Ecological information

Toxicity

: Very toxic to aquatic life with long lasting effects. Very toxic to aquatic life. Ecology - general

Nonylphenols (25154-52-3)		
LC50 fishes 1	0.135 mg/l 96 Hr Pimephales promelas [flow-through]	
EC50 Daphnia 1	0.0874 - 0.124 48 Hr Daphnia magna [semi-static]	
EC50 other aquatic organisms 1	0.41 mg/l 96 Hr Pseudokirchneriella subcapitata (freshwater algae)	

Persistence and degradability

No additional information available

04/28/2015 C1 Extra Slow Catalyst 5/1

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities.

No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the

product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN2735 Polyamines, liquid, corrosive, n.o.s. (Polyoxypropylenediamine), 8, III

UN-No.(DOT) : 2735 DOT NA no. : UN2735

Proper Shipping Name (DOT) : Amines, liquid, corrosive, n.o.s. (Polyoxypropylenediamine)

Department of Transportation (DOT) Hazard

Classes

: 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger

DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 52 - Stow "separated from" acids

Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

C1 Extra Slow Catalyst

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

Nonylphenols	CAS #:	(25154-52-3)	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ			lb
Section 313		Listed on US SARA Section 313	

15.2. International regulations

04/28/2015 C1 Extra Slow Catalyst 6/1

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CANADA

No additional information available.

15.3. US State regulations

California Proposition 65

This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

1,3-Benzenedimethanamine (1477-55-0)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) List

Nonylphenols (25154-52-3)

- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) List

Trimethylhexamethylenediamine (25620-58-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Indication of changes : Revision 1.0: New SDS Created.

Revision date : 04/28/2015 Other information : Author: NMR.

NFPA health hazard : 3 - Short exposure could cause serious temporary or


residual injury even though prompt medical attention was

given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health: 3*Flammability: 0Physical: 0Personal Protection:

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material.

04/28/2015 C1 Extra Slow Catalyst 7/1