

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 01/22/2016 Version: 2.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

Mixture

#### 1.1. Product identifier

Product name Product form

- : TuffStuff 1284 Gray
- 1.2 Relevant identified u
  - . Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

New Nautical Coatings, Inc. Sea Hawk Premium Yacht Finishes 14805 49th Street North Clearwater, FL 33762 USA Only: 1-800-528-0997 International: (727) 523-8053

#### 1.4. Emergency telephone numbers

Emergency number

- : CHEMTREC day or night inside USA & Canada 1-800-424-9300
- : CHEMTREC day or night outside USA & Canada +1-703-741-5970
- : Poison Control Center 1-800-222-1222

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification (GHS-US)

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Skin Sens. 1	H317
Carc. 2	H351
STOT RE 2	H373
Aquatic Acute 2	H401
Aquatic Chronic 2	H411

#### 2.2. Label elements

#### GHS-US labeling

Hazard pictograms (GHS-US)

Signal word (GHS-US)

Hazard statements (GHS-US)

Precautionary statements (GHS-US)



#### : Warning

- : H226 Flammable liquid and vapor
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H351 Suspected of causing cancer
- H373 May cause damage to organs through prolonged or repeated exposure
- H401 Toxic to aquatic life
- H411 Toxic to aquatic life with long lasting effects
- : P201 Obtain special instructions before use
  - P202 Do not handle until all safety precautions have been read and understood
  - P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
  - P233 Keep container tightly closed
  - P240 Ground/bond container and receiving equipment
  - P241 Use explosion-proof electrical/ventilating/lighting equipment
  - P242 Use only non-sparking tools
  - P243 Take precautionary measures against static discharge
  - P260 Do not breathe dust, fume, mist, spray, vapors
  - P261 Avoid breathing dust, fume, gas, mist, spray, vapors
- P264 Wash hands, forearms and face thoroughly after handling
- P272 Contaminated work clothing must not be allowed out of the workplace

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear eye protection, protective gloves, protective clothing P302+P352 - If on skin: Wash with plenty of soap and water P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P308+P313 - If exposed or concerned: Get medical advice/attention P314 - Get medical advice/attention if you feel unwell P321 - Specific treatment (see first aid instructions on this label) P332+P313 - If skin irritation occurs: Get medical advice/attention P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P370+P378 - In case of fire: Use carbon dioxide, dry powder, alcohol resistant foam or sand to extinguish P391 - Collect spillage P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

#### 2.3. Other hazards

Other hazards not contributing to the classification

: None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

#### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

. .

3.2. Mixture

Name	Product identifier	%
Bisphenol A diglycidyl ether - bisphenol A copolymer	(CAS No) 25036-25-3	15 - 40
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	15 - 40
Titanium dioxide	(CAS No) 13463-67-7	7 - 13
Trizinc diphosphate	(CAS No) 7779-90-0	7 - 13
Silane, dichlorodimethyl-, reaction products with silica	(CAS No) 68611-44-9	1 - 5
Phosphoric acid, barium salt (2:3)	(CAS No) 13517-08-3	1 - 5
Methyl isobutyl ketone	(CAS No) 108-10-1	1 - 5
Ethylbenzene	(CAS No) 100-41-4	0.1 - 1

### **SECTION 4: First aid measures**

Dependention of first and measures

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.
IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention if you feel unwell.
both acute and delayed
Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.
May cause respiratory irritation.
Causes skin irritation. May cause an allergic skin reaction.
Causes serious eye irritation.
May cause gastrointestinal irritation.
Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting mea	asures	
5.1. Extinguishing media		
Suitable extinguishing media	: Carbon dioxide. Dry powder. Alcohol-resistant foam. Sand.	
5.2. Special hazards arising fro	Special hazards arising from the substance or mixture	
Fire hazard	: Flammable liquid and vapor.	
Explosion hazard	: No data available.	
Reactivity	: No dangerous reactions known under normal conditions of use.	
5.3. Advice for firefighters		
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.	
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.	
SECTION 6: Accidental relea	ise measures	
6.1. Personal precautions, pro	Personal precautions, protective equipment and emergency procedures	
6.1.1. For non-emergency perso	nnel	
Protective equipment	: Wear Protective equipment as described in Section 8.	
Emergency procedures	: Evacuate unnecessary personnel.	
C 4 2 For an an an an an an an an		

### 6.1.2. For emergency responders

Protective equipment

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

respirator, in case of emergency.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Scoop solid spill into closing containers or bags. Small quantities of liquid spill: take u in non-combustible absorbent material and shovel into container for disposal.
Methods for cleaning up	<ul> <li>Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).</li> <li>Exclude sources of ignition and ventilate the area. Waste from this product may be hazardous as defined under RCRA (40 CFR 261).</li> </ul>

#### 6.4. Reference to other sections

No additional information available

SECT	ION 7: Handling and storage	
7.1.	Precautions for safe handling	
Preca	autions for safe handling	Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Containers of this material may be hazardous when emptied. Do not breathe mist, spray.
	Our little of the sector of the sector is the sector	· · · · · · · · · · · · · · · · · · ·

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from: Direct sunlight, Heat sources. Keep container closed when not in use.

: Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air

### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Bisphenol A diglycidyl ether - bisphenol A copolymer (25036-25-3)		
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
ACGIH TWA (ppm)	100 ppm	
ACGIH STEL (ppm)	150 ppm	
OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>	
OSHA PEL (TWA) (ppm)	100 ppm	
OSHA PEL (STEL) (mg/m <sup>3</sup> )	655 mg/m <sup>3</sup>	

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylenes (o-, m-, p- isomers) (1330-20-7)	
OSHA PEL (STEL) (ppm)	150 ppm
Ethylbenzene (100-41-4)	
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	upper respiratory tract irritation; kidney damage
	(nephropathy); cochlear impairment
OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
OSHA PEL (STEL) (ppm)	125 ppm
	120 ppm
Toluene (108-88-3)	00
ACGIH TWA (ppm) Remark (ACGIH)	20 ppm Visual impair; female repro;
	visuai impail, iemaie iepio,
Benzene (71-43-2)	0.5
ACGIH TWA (ppm) ACGIH STEL (ppm)	0.5 ppm
OSHA PEL (TWA) (ppm)	2.5 ppm 1 ppm
OSHA PEL (STEL) (ppm)	5 ppm (see 29 CFR 1910.1028)
OSHA PEL (Ceiling) (ppm)	25 ppm
Silane, dichlorodimethyl-, reaction products with	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Titanium dioxide (13463-67-7)	
ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> total dust
Arsenic (7440-38-2)	
ACGIH TWA (mg/m <sup>3</sup> )	0.01 mg/m <sup>3</sup>
Remark (ACGIH)	Lung cancer
OSHA PEL (TWA) (mg/m <sup>3</sup> )	0.5 mg/m <sup>3</sup>
Nickel (7440-02-0)	
ACGIH TWA (mg/m <sup>3</sup> )	1.5 mg/m <sup>3</sup> (inhalable fraction)
OSHA PEL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
Trizinc diphosphate (7779-90-0)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Phosphoric acid, barium salt (2:3) (13517-08-3)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
. ,	
Lead (7439-92-1)	0.05 mg/m3
ACGIH TWA (mg/m <sup>3</sup> ) Remark (ACGIH)	0.05 mg/m <sup>3</sup> CNS & PNS impair
OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 μg/m <sup>3</sup>
Silica: Crystalline, quartz (14808-60-7)	
ACGIH TWA (mg/m <sup>3</sup> ) OSHA PEL (TWA) (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction) (30)/(%SiO2 + 2) total dust; (10)/(%SiO2 + 2)
OSHA PEL (TWA) (IIIg/III')	respirable fraction $(10)/(3002 + 2)$
OSHA PEL (TWA) (ppm)	(250)/(%SiO2 + 5) respirable fraction
Methyl isobutyl ketone (108-10-1)	
ACGIH TWA (ppm)	20 ppm
ACGIH STEL (ppm)	75 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	410 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	100 ppm
	I.

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 0 2 ontrol

8.2. E	Exposure controls		
Appropria	ate engineering controls	Provide adequate general and local exhaust ventilation. Use process enclosures, local ex ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequa ventilation, especially in confined areas.	
Personal	protective equipment	: Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.	
Hand pro	tection	: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested g materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol lamin PVC or vinyl. Suitable gloves for this specific application can be recommended by the glo supplier.	love ate,
Eye prote	ection	: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.	у
Skin and	body protection	: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure	э.
Respirato	ory protection	Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pre mode with emergency escape provisions. In case of inadequate ventilation or risk of inhal of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pres air-supplied respirator if there is any potential for an uncontrolled release, exposure levels not known, or any other circumstances where air-purifying respirators may not provide adequate protection.	lation ssure

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and	chemical properties
Physical state	: Liquid
Color	: Gray.
Odor	: No data available
Odor Threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 27.22 °C (81F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.34 g/cm <sup>3</sup>
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available
0.0 Other information	

#### 9.2. Other information

No additional information available

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremely high or low temperatures. Direct sunlight.

#### Incompatible materials 10.5.

No data available.

#### 10.6. Hazardous decomposition products

No data available.

#### **SECTION 11: Toxicological information**

#### Information on toxicological effects 11.1.

Acute toxicity	: Not classified
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (gases)	4500.000 ppmV/4h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
Ethylbenzene (100-41-4)	·
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
ATE CLP (gases)	4500.000 ppmV/4h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
Benzene (71-43-2)	·
LD50 dermal rabbit	> 8200 mg/kg
LC50 inhalation rat (mg/l)	44.66 mg/l/4h (vapor)
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg (Source: IUCLID)
Arsenic (7440-38-2)	
LD50 oral rat	15 mg/kg
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (gases)	700.000 ppmV/4h
ATE CLP (vapors)	3.000 mg/l/4h
ATE CLP (dust, mist)	0.500 mg/l/4h
Nickel (7440-02-0)	
LD50 oral rat	> 9000 mg/kg
Trizinc diphosphate (7779-90-0)	
LD50 oral rat	> 5000 mg/kg
LDJU Ulai lat	> bood mg/kg
Silica: Crystalline, quartz (14808-60-7)	> ooo mang
	500 mg/kg
Silica: Crystalline, quartz (14808-60-7)	
Silica: Crystalline, quartz (14808-60-7) LD50 oral rat	
Silica: Crystalline, quartz (14808-60-7) LD50 oral rat Methyl isobutyl ketone (108-10-1)	500 mg/kg
Silica: Crystalline, quartz (14808-60-7) LD50 oral rat Methyl isobutyl ketone (108-10-1) LD50 oral rat	500 mg/kg 2080 mg/kg
Silica: Crystalline, quartz (14808-60-7) LD50 oral rat Methyl isobutyl ketone (108-10-1) LD50 oral rat LD50 dermal rabbit	500 mg/kg 2080 mg/kg 3000 mg/kg
Silica: Crystalline, quartz (14808-60-7) LD50 oral rat Methyl isobutyl ketone (108-10-1) LD50 oral rat LD50 dermal rabbit ATE CLP (gases)	2080 mg/kg 2080 mg/kg 3000 mg/kg 4500.000 ppmV/4h

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Prepared according to Federal Register / Vol. 77, No. 58 / N	
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable
Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Benzene (71-43-2)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens
Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
Arsenic (7440-38-2)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens
Nickel (7440-02-0)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
Lead (7439-92-1)	
IARC group	2A - Probably carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
Silica: Crystalline, quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Methyl isobutyl ketone (108-10-1)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May cause gastrointestinal irritation.
Chronic symptoms	: Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - general

: Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

	• •	
	TuffStuff 1284 Gray	
	Persistence and degradability	Not established.
12.3. Bioaccumulative potential No additional information available		
12 No	4. Mobility in soil additional information available	

#### 12.5. Other adverse effects

No additional information available

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	· · ·
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste treatment methods	: Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.
SECTION 14: Transport information	
In accordance with DOT	
Transport document description	: UN1263 Paint related material (including paint thinning, drying, removing, or reducing compound), 3, III
UN-No.(DOT)	: 1263
DOT NA no.	: UN1263
Proper Shipping Name (DOT)	: Paint related material
	including paint thinning, drying, removing, or reducing compound
Department of Transportation (DOT) Hazard Classes	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid
Packing group (DOT)	: III - Minor Danger
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Additional information	
Other information	: No supplementary information available.
Transport by sea	
No additional information available	
Air transport	

#### Air transport

No additional information available

# **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

### TuffStuff 1284 Gray

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

Xylene (mixed isomers)	CAS #:	1330-20-7	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		100	lb
Section 313		Listed on US SARA Section 313	

Ethylbenzene	CAS #:	100-41-4	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		1000	lb
Section 313		Listed on US SARA Section 313	

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isobutyl Alcohol	CAS #:	78-83-1	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		5000	lb
Section 313	Not	Listed on US SARA Section 313	

Toluene	CAS #:	108-88-3	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		1000	lb
Section 313		Listed on US SARA Section 313	

Benzene	CAS #:	71-43-2	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		10	lb
Section 313		Listed on US SARA Section 313	

Butyl acetate	CAS #:	123-86-4	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		5000	lb
Section 313		Listed on US SARA Section 313	

Arsenic	CAS #:	7440-38-2	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		1	lb
Section 313		Listed on US SARA Section 313	

Chromium	CAS #:	7440-47-3	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		5000	lb
Section 313		Listed on US SARA Section 313	

Nickel	CAS #:	7440-02-0	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		100	lb
Section 313		Listed on US SARA Section 313	

Lead

CAS #: 7439-92-1

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Section 302 (EHS) TPQ		lb
Section 304 EHS RQ		lb
CERCLA RQ	10	lb
Section 313	Listed on US SARA Section 313	

Cadmium	CAS #:	7440-43-9	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		10	lb
Section 313		Listed on US SARA Section 313	

Arsenic	CAS #:	7440-38-2	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		1	lb
Section 313		Listed on US SARA Section 313	

Copper	CAS #:	7440-50-8	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		5000	lb
Section 313		Listed on US SARA Section 313	

Manganese	CAS #:	7439-96-5	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ			lb
Section 313		Listed on US SARA Section 313	

Methyl isobutyl ketone	CAS #:	108-10-1	
Section 302 (EHS) TPQ			lb
Section 304 EHS RQ			lb
CERCLA RQ		5000	lb
Section 313		Listed on US SARA Section 313	

#### 15.2. International regulations

#### CANADA

No additional information available.

#### 15.3. US State regulations

#### **California Proposition 65**

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

Ethylbenzene (100-41-4)				
U.S California -	U.S California -	U.S California -	U.S California -	No significance risk
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	level (NSRL)

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylbenzene (100-41-	-4)			
Yes	No	No	No	
Toluene (108-88-3)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	
Benzene (71-43-2)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	Yes	

Titanium dioxide (13463-	67-7)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Arsenic (7440-38-2)		•		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	No	
Nickel (7440-02-0)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Lead (7439-92-1)	J	1		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	Yes	Yes	
Silica: Crystalline, guartz	z (14808-60-7)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Methyl isobutyl ketone (1	108-10-1)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	No	
Xylenes (o-, m-, p- isome	ers) (1330-20-7)			
	ght To Know List to Know Hazardous Substanc (Right to Know) - Environmer			
Ethylbenzene (100-41-4)				
U.S New Jersey - Right U.S Massachusetts - Rig	to Know Hazardous Substanc ght To Know List : (Right to Know) - Environmer			

#### Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Toluene (108-88-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

### Benzene (71-43-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

#### Titanium dioxide (13463-67-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

#### Arsenic (7440-38-2)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances

#### Nickel (7440-02-0)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances

#### Lead (7439-92-1)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

#### Silica: Crystalline, guartz (14808-60-7)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

#### Methyl isobutyl ketone (108-10-1)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

### **SECTION 16: Other information**

Indication of changes Revision date Other information	: Revision 1.0: New SDS Created. : 03/23/2015 : Author: NMR.
NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2*
Flammability	: 1

Personal Protection

### Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility of presonal injury or property damage to vendors, users, or third-parties caused by this material.