

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Wax N Grease Killer

Product form : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

New Nautical Coatings, Inc.  
Sea Hawk Premium Yacht Finishes  
14805 49th Street North  
Clearwater, FL 33762  
USA Only: 1-800-528-0997  
International: (727) 523-8053

#### 1.4. Emergency telephone numbers

Emergency number : CHEMTREC day or night inside USA & Canada  
1-800-424-9300  
: CHEMTREC day or night outside USA & Canada  
+1-703-741-5970  
: Poison Control Center  
1-800-222-1222

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Liq. 3 H226  
Skin Irrit. 2 H315  
Muta. 1B H340  
Carc. 1B H350  
STOT RE 1 H372  
Asp. Tox. 1 H304  
Aquatic Chronic 3 H412

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02



GHS07



GHS08

Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H340 - May cause genetic defects  
H350 - May cause cancer  
H372 - Causes damage to organs through prolonged or repeated exposure  
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical/ventilating/lighting equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe dust, fume, mist, spray, vapors  
P264 - Wash hands, forearms and face thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P273 - Avoid release to the environment  
P280 - Wear eye protection, protective gloves, protective clothing

# Wax N Grease Killer

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P301+P310 - IF SWALLOWED: Immediately call a doctor  
P302+P352 - If on skin: Wash with plenty of soap and water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P314 - Get medical advice/attention if you feel unwell  
P321 - Specific treatment (see first aid instructions on this label)  
P331 - Do NOT induce vomiting  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use carbon dioxide, dry powder, alcohol resistant foam, or sand to extinguish  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name                                       | Product identifier  | %       |
|--|---------------------|---------|
| Xylenes (o-, m-, p- isomers)               | (CAS No) 1330-20-7  | 30 - 60 |
| Stoddard solvent                           | (CAS No) 8052-41-3  | 30 - 60 |
| Ethylbenzene                               | (CAS No) 100-41-4   | 10 - 30 |
| Solvent naphtha, petroleum, light aromatic | (CAS No) 64742-95-6 | 10 - 30 |
| Benzene, 1,2,4-trimethyl-                  | (CAS No) 95-63-6    | 5 - 10  |
| Cumene                                     | (CAS No) 98-82-8    | 0.1 - 1 |

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause cancer. May cause damage to organs through prolonged or repeated exposure.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction. Harmful in contact with skin.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

Chronic symptoms : May cause cancer. May cause damage to organs through prolonged or repeated exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Alcohol-resistant foam. Sand.

# Wax N Grease Killer

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.  
Explosion hazard : No data available.  
Reactivity : No dangerous reactions known under normal conditions of use.

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.  
Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.  
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Exclude sources of ignition and ventilate the area. Waste from this product may be hazardous as defined under RCRA (40 CFR 261).

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Containers of this material may be hazardous when emptied. . Do not breathe mist, spray.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from: Direct sunlight, Heat sources. Keep container closed when not in use.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Xylenes (o-, m-, p- isomers) (1330-20-7) |  |
|--|--|
| ACGIH TWA (ppm)                          | 100 ppm  |
| ACGIH STEL (ppm)                         | 150 ppm  |
| OSHA PEL (TWA) (mg/m³)                   | 435 mg/m³  |
| OSHA PEL (TWA) (ppm)                     | 100 ppm  |
| OSHA PEL (STEL) (mg/m³)                  | 655 mg/m³  |
| OSHA PEL (STEL) (ppm)                    | 150 ppm  |
| Ethylbenzene (100-41-4)                  |  |
| ACGIH TWA (ppm)                          | 20 ppm   |
| Remark (ACGIH)                           | upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment |
| OSHA PEL (TWA) (mg/m³)                   | 435 mg/m³  |
| OSHA PEL (TWA) (ppm)                     | 100 ppm  |

# Wax N Grease Killer

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |  |
|--|--|
| <b>Ethylbenzene (100-41-4)</b>                                 |  |
| OSHA PEL (STEL) (mg/m³)  | 545 mg/m³  |
| OSHA PEL (STEL) (ppm)  | 125 ppm  |
| <b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b> |  |
| Remark (ACGIH)   | OELs not established                                 |
| Remark (OSHA)  | OELs not established                                 |
| <b>Stoddard solvent (8052-41-3)</b>                            |  |
| ACGIH TWA (ppm)  | 100 ppm  |
| Remark (ACGIH)   | CNS impairment; Eye, skin, and kidney damage; nausea |
| OSHA PEL (TWA) (mg/m³)   | 2900 mg/m³   |
| OSHA PEL (TWA) (ppm)   | 500 ppm  |
| <b>Cumene (98-82-8)</b>  |  |
| ACGIH TWA (ppm)  | 50 ppm   |
| OSHA PEL (TWA) (mg/m³)   | 245 mg/m³  |
| OSHA PEL (TWA) (ppm)   | 50 ppm   |
| <b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>                     |  |
| Remark (ACGIH)   | OELs not established                                 |
| Remark (OSHA)  | OELs not established                                 |

### 8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.



Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. . Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection

: Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |                     |
|---|---------------------|
| Physical state                              | : Liquid            |
| Color                                       | : Clear.            |
| Odor  | : No data available |
| Odor Threshold                              | : No data available |
| pH  | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Melting point                               | : No data available |
| Freezing point                              | : No data available |
| Boiling point                               | : No data available |
| Flash point                                 | : 27.2 °C (81F)     |
| Auto-ignition temperature                   | : No data available |

# Wax N Grease Killer

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                 |                          |
|---------------------------------|--------------------------|
| Decomposition temperature       | : No data available      |
| Flammability (solid, gas)       | : No data available      |
| Vapor pressure                  | : No data available      |
| Relative vapor density at 20 °C | : No data available      |
| Relative density                | : No data available      |
| Specific gravity / density      | : 0.87 g/cm <sup>3</sup> |
| Solubility                      | : No data available      |
| Log Pow                         | : No data available      |
| Log Kow                         | : No data available      |
| Viscosity, kinematic            | : No data available      |
| Viscosity, dynamic              | : No data available      |
| Explosive properties            | : No data available      |
| Oxidizing properties            | : No data available      |
| Explosion limits                | : No data available      |

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremely high or low temperatures. Direct sunlight.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

No data available.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

| Xylenes (o-, m-, p- isomers) (1330-20-7)                |                            |
|---|----------------------------|
| LD50 oral rat   | 3500 mg/kg                 |
| ATE CLP (dermal)  | 1100.000 mg/kg body weight |
| ATE CLP (gases)   | 4500.000 ppmV/4h           |
| ATE CLP (vapors)  | 11.000 mg/l/4h             |
| ATE CLP (dust, mist)                                    | 1.500 mg/l/4h              |
| Ethylbenzene (100-41-4)                                 |                            |
| LD50 oral rat   | 3500 mg/kg                 |
| LD50 dermal rabbit                                      | 15400 mg/kg                |
| LC50 inhalation rat (mg/l)                              | 17.2 mg/l/4h               |
| ATE CLP (gases)   | 4500.000 ppmV/4h           |
| ATE CLP (vapors)  | 11.000 mg/l/4h             |
| ATE CLP (dust, mist)                                    | 1.500 mg/l/4h              |
| Solvent naphtha, petroleum, light aromatic (64742-95-6) |                            |
| LD50 dermal rabbit                                      | > 2000 mg/kg               |
| LC50 inhalation rat (ppm)                               | 3400 ppm/4h                |
| Cumene (98-82-8)  |                            |
| LD50 dermal rabbit                                      | 12300 µl/kg                |
| LC50 inhalation rat (ppm)                               | > 3577 ppm 6 h             |
| Benzene, 1,2,4-trimethyl- (95-63-6)                     |                            |
| LD50 oral rat   | 3280 mg/kg                 |

# Wax N Grease Killer

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Benzene, 1,2,4-trimethyl- (95-63-6)</b> |                  |
|--|------------------|
| LD50 dermal rabbit                         | > 3160 mg/kg     |
| ATE CLP (gases)                            | 4500.000 ppmV/4h |
| ATE CLP (vapors)                           | 11.000 mg/l/4h   |
| ATE CLP (dust, mist)                       | 1.500 mg/l/4h    |

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : May cause genetic defects.  
Carcinogenicity : May cause cancer.

| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b> |                      |
|---|----------------------|
| IARC group                                      | 3 - Not classifiable |

| <b>Ethylbenzene (100-41-4)</b> |                                      |
|--------------------------------|--------------------------------------|
| IARC group                     | 2B - Possibly carcinogenic to humans |

| <b>Cumene (98-82-8)</b> |                                      |
|-------------------------|--------------------------------------|
| IARC group              | 2B - Possibly carcinogenic to humans |

Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : Not classified  
Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure.  
Aspiration hazard : May be fatal if swallowed and enters airways.  
Symptoms/injuries after inhalation : May cause respiratory irritation.  
Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction. Harmful in contact with skin.  
Symptoms/injuries after eye contact : Causes serious eye damage.  
Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.  
Chronic symptoms : May cause cancer. May cause damage to organs through prolonged or repeated exposure.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects

### 12.2. Persistence and degradability

| <b>Wax N Grease Killer</b>    |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.  
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

## SECTION 14: Transport information

In accordance with DOT  
Transport document description : UN1993 Flammable liquids, n.o.s. (Contains: Xylene, Ethylbenzene), 3, II  
UN-No.(DOT) : 1993  
DOT NA no. : UN1993  
Proper Shipping Name (DOT) : Flammable liquids, n.o.s (Contains: Xylene, Ethylbenzene)  
Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

# Wax N Grease Killer

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Quantity Limitations Passenger aircraft/rail : 5 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L  
CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

### Additional information

Other information : No supplementary information available.

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

|   |         |
|---|---------|
| <b>Wax N Grease Killer</b>  |         |
| All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory |         |
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>   |         |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory   |         |
| Listed on United States SARA Section 313  |         |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) :  | 100 lb  |
| SARA Section 313  | Listed  |
| <b>Ethylbenzene (100-41-4)</b>  |         |
| Listed on United States SARA Section 313  |         |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) :  | 1000 lb |
| SARA Section 313  | Listed  |
| <b>Cumene (98-82-8)</b>   |         |
| Listed on United States SARA Section 313  |         |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) :  | 5000 lb |
| SARA Section 313  | Listed  |
| <b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>  |         |
| Listed on United States SARA Section 313  |         |
| SARA Section 313  | Listed  |

### 15.2. International regulations

#### CANADA

No additional information available.

### 15.3. US State regulations

#### California Proposition 65

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

# Wax N Grease Killer

## Safety Data Sheet


Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |   |   |   |                                   |
|--|---|---|---|-----------------------------------|
| <b>Ethylbenzene (100-41-4)</b>   |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List  | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes  | No  | No  | No  |                                   |
| <b>Cumene (98-82-8)</b>  |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List  | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes  | No  | No  | No  |                                   |
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>  |   |   |   |                                   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |   |   |   |                                   |
| <b>Ethylbenzene (100-41-4)</b>   |   |   |   |                                   |
| U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Massachusetts - Right To Know List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |   |   |   |                                   |
| <b>Stoddard solvent (8052-41-3)</b>  |   |   |   |                                   |
| U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Massachusetts - Right To Know List<br>U.S. - Pennsylvania - RTK (Right to Know) List                        |   |   |   |                                   |
| <b>Cumene (98-82-8)</b>  |   |   |   |                                   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |   |   |   |                                   |
| <b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>   |   |   |   |                                   |
| U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Massachusetts - Right To Know List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |   |   |   |                                   |

### SECTION 16: Other information

Indication of changes : Revision 1.0: New SDS Created.  
Revision date : 03/20/2015  
Other information : Author: NMR.

NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.  
NFPA fire hazard : 1 - Must be preheated before ignition can occur.  
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 3\*  
Flammability : 1  
Physical : 0  
Personal Protection : Splash goggles, Gloves, Synthetic apron, Vapor respirator

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material.