

PREMIUM YACHT FINISHES Date of issue: 07/28/2015 Revision date: 07/28/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Biocop TF
Product form : liquid
Other means of identification : 1200-1 series

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Antifouling

1.3. Details of the supplier of the safety data sheet

Sea Hawk Paints Oceania Distribution Warehouse 6 Ross Place Wetherill Park Sydney, Australia, 2164 Australia Only: (+61)404 721 721 International: (727) 523-8053

1.4. Emergency telephone number

For Hazardous Materials [or Dangerous Goods] Incident spill, leaks, fire, Exposure, or Accident

Call CHEMTREC 24 hours 7 days per week

Emergency number : CHEMTREC Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Emergency number : CHEMTREC Within USA and Canada: 1-800-424-9300 CCN155

Emergency number : Australia Local 61-290372994

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 3 H226 Acute Tox. 4 H302 Asp. Tox. 1 H304 Eye Dam.1 H318 Aquatic Chronic 1 H410 Aquatic Acute 1 H400 Skin Sens. 1 H317 Carc. 1A H350 Muta. 1B H340

Contains 10.94% ingredients of unknown oral toxicity.

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS06







Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Fammable liquid and vapor

H302 - Harmful if swallowed

H304- May be fatal if swallowed and enters airways

H317- May cause an allergic skin reaction

H318- Causes serious eye damage H340- May cause genetic defects

H350- May cause cancer

H400- Very toxic to aquatic life

H410- Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) : P201 – Obtain special instructions before use.

P202 - Do not handle until all safety percautions have been read and understood P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

07/28/2015 Biocop TF Page 1

P233 - Keep container tightly closed

P235 - Keep Cool

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion proof equipment.

P242 – Use non-sparking tools.

P243 – Take action to prevent static discharge.

P261 - Avoid breathing dust/fume/mist/vapors/spray

P264 - Wash face, hands and forearms thoroughly after handling

P270 – Do not eat, drink, or smoke when using this product

P272 – Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the envirment

P280 - Wear eye protection, protective clothing, protective gloves, face protection

P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

P302+P352 - IF ON SKIN: wash with plenty of soap and water

 $P303 + P353 + P361 + P364 - IF\ ON\ SKIN\ (or\ hair):\ Take\ off\ immediately\ all\ contaminated\ clothing\ and\ wash\ before\ reuse.\ Rinse\ skin\ with\ water.$

P305+P351+P338- IF IN EYE: Rinse continuously with water for several minutes. Remove contact lense if present and easy to do- continue rinsing

P308+P313 - If exposed or concerned: Get medical advice/attention

P310 – Immediately call a POISON CENTER or doctor if in eyes.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P321 - Specific treatment (see first aid instructions on this label)

P330 - Rinse mouth.

P331 - Do NOT induce vomiting

P332+P313 – If eye irritation persist: Get medical advice/attentionP333+P313- If skin irritation or a rash occurs:Get medical advice/attentionP362+P364- Take off contaminated clothing and wash before use

P370+P378 – In case of fire: Use carbon dioxide, dry powder, alcohol-resistant foam or water spray to extinguish.

P391- Collect spillage

P403- Store in a well ventilated place.

P405- Store locked up

P501 - Dispose of contents/container to licensed waste handling facility

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Sdstance type:

: Multi-constituent

Name	Product identifier	0%
Solvent naphtha(petroleum), light aromatic	(CAS No) 64742-95-6	10-25
Ethylbenzene	(CAS No) 100-41-4	0.01 - 1
Cupric oxide	(CAS No) 1317-38-0	3-10
Zinc oxide	(CAS No) 1314-13-2	1-10
Cuprous oxide	(CAS No) 1317-39-1	35-50
Zinc pyrithione	(CAS No) 13463-41-7	4-10
Cumene	(CAS No) 98-82-8	0.1-1
Pseudocumene	(CAS No) 95-63-6	5-10
Xylene	(CAS No) 1330-20-7	0.1-1
Rosin x50	(CAS No) 8050-09-7	5-10
Toluene	(CAS No) 108-88-3	Trace
Benzene	(CAS No) 71-43-2	Trace
Amorphous Silica	(CAS No) 7631-86-9	0.1-1
Arsenic	(CAS No) 7440-38-2	0.1-1
Nickel	(CAS No) 7440-02-0	0.1-1
C18-28 Long Chain Chlorinated Paraffins	(CAS No) 63449-39-8	0.1-1
Talc	(CAS No) 14807-96-6	5-10
Crystalline silica (quartz)	(CAS No) 14808-60-7	0.1-1
Lead	(CAS No) 7439-92-1	0.1-1
2-Pyridol, 1-Oxide	(CAS No) 13161-30-3	0.1-1

07/28/2015 **Biocop TF** 2/13

Safety Data Sheet

Full text of H-phases: see section 16

3.2. Mixture
Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the

label where possible).

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a

POISON CENTER or doctor/physician.

First-aid measures after skin contact : IF ON SKIN: Immediately rinse with plenty of water (for at least 15 minutes). Get immediate medical

advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes

minimum). Get medical advice/attention.

First-aid measures after ingestion : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May be fatal if swallowed and enters airways. .

Symptoms/injuries after skin contact : May cause an allergic skin reaction
Symptoms/injuries after eye contact : Causes serious eye damage.
Symptoms/injuries after ingestion : Harmful if swallowed.

Chronic symptoms : May cause genetic defects. May cause cancer.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder.Alcohol-resistant foam.Water spray.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor. May produce carbon oxides under fire conditions.

Explosion hazard : Product is not explosive.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Do not dispose of fire-fighting water in the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-

contained breathing apparatus and protective suit (see item 8).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly

equipped with respiratory equipment and full chemical protective gear (see Section 8).

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Wear approved supplied-air

respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Exclude sources of ignition and ventilate the area. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the

waste regulations (see Section 13). Waste from this product may be hazardous.

6.4. Reference to other sections

No additional information available

07/28/2015 **Biocop TF** 3/13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition - No smoking. Use appropriate personal protection equipment (PPE).

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep

container closed when not in use.

Storage temperature

< 38 °C (100°F)

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Copper(I) oxide (1317-39-1)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Copper oxide (CuO) (1317-38-0)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Solvent naphtha, petroleum, light aromatic (6	4742-95-6)
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Cumene (98-82-8)	
ACGIH TWA (ppm)	50 ppm
OSHA PEL (TWA) (mg/m³)	245 mg/m ³
OSHA PEL (TWA) (ppm)	50 ppm
Benzene, 1,2,4-trimethyl- (95-63-6)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Xylenes (o-, m-, p- isomers) (1330-20-7)	<u>l</u>
ACGIH TWA (ppm)	100 ppm
ACGIH STEL (ppm)	150 ppm
OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m³)	655 mg/m³
OSHA PEL (STEL) (ppm)	150 ppm
Ethylbenzene (100-41-4)	
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment
OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m³)	545 mg/m³
OSHA PEL (STEL) (ppm)	125 ppm
Rosin (8050-09-7)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Toluene (108-88-3)	· ·
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	Visual impair; female repro;
Benzene (71-43-2)	
ACGIH TWA (ppm)	0.5 ppm
ACGIH STEL (ppm)	2.5 ppm

07/28/2015 **Biocop TF** 4/13

Safety Data Sheet

Copper(I) oxide (1317-39-1)	
OSHA PEL (TWA) (ppm)	1 ppm
OSHA PEL (STEL) (ppm)	5 ppm (see 29 CFR 1910.1028)
· / 41 /	** '
OSHA PEL (Ceiling) (ppm)	25 ppm
Silica, amorphous (7631-86-9)	
Remark (ACGIH)	OELs not established
OSHA PEL (TWA) (ppm)	20 mppcf (80)/(% SiO2) mg/m3
Arsenic (7440-38-2)	
ACGIH TWA (mg/m³)	0.01 mg/m ³
Remark (ACGIH)	Lung cancer
OSHA PEL (TWA) (mg/m³)	0.5 mg/m^3
Chlorinated paraffin waxes and hydrocarbon	waxes (63449-39-8)
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Silica: Crystalline, quartz (14808-60-7)	<u> </u>
ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
OSHA PEL (TWA) (mg/m³)	(10)/(%SiO2 + 2) total dust; $(10)/(%SiO2 + 2)$ respirable fraction
OSHA PEL (TWA) (ppm)	(250)/(%SiO2 + 5) respirable fraction
Talc (14807-96-6)	
ACGIH TWA (mg/m³)	2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction
OSHA PEL (TWA) (ppm)	20 mppcf if 1% Quartz or more, use Quartz limit
Zinc oxide (1314-13-2)	
ACGIH TWA (mg/m³)	2 mg/m³ (respirable fraction)
ACGIH STEL (mg/m³)	10 mg/m³ (respirable fraction)
Remark (ACGIH)	Metal fume fever
OSHA PEL (TWA) (mg/m³)	5 mg/m³ (respirable fraction)
OSHA PEL (STEL) (mg/m³)	10 mg/m³ (fume)
Zeolite (1318-02-1)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Zinc pyrithione (13463-41-7)	l
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
2-Hydroxypyridine 1-oxide (13161-30-3)	l
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

8.2. Exposure controls

Appropriate engineering controls Personal protective equipment

- : Ensure adequate ventilation, especially in confined areas. Handle with good industrial hygiene and safety.
- : Face shield. Respiratory protection of the dependent type. Gloves. Protective goggles. Protective clothing.









Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl

Eye protection

: Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

: Wear long sleeves. Handle with gloves

Respiratory protection

: An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits.

07/28/2015 **Biocop TF** 5/13

Safety Data Sheet

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical propertiesPhysical state : Liquid

Appearance : liquid

Color : Light Blue, Dark Blue, Green, Red, Teal, Grey and Black

Odor Aromatic odour. Odor Threshold No data available No data available pН Relative evaporation rate (butyl acetate=1) Not Measured Relative evaporation rate (ether=1) Not Measured Melting point No data available Freezing point : No data available Not Measured Boiling point

Flash point : 38°C (101°F)-closed cup

Self ignition temperature : Na data avilable

Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapor pressure : Not Measured Relative vapor density at 20 °C : Heavier than air

Relative density : 2.07 g/ml at 25°C (77°F)

Solubility : Water: None Log Pow No data available Log Kow No data available Viscosity, kinematic : No data available Viscosity, dynamic No data available Explosive properties No data available Oxidizing properties No data available Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion:CO and CO2 are formed.Reacts violently with (strong) oxidizers:(increased)risk of fire/explosion.reacts with (some) acids.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremes of tempearture and direct sunlight.

10.5. Incompatible materials

Avoid contact with: Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Copper(I) oxide (1317-39-1)		
LD50 oral rat	470 mg/kg	
LD50 dermal rat	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	5 mg/l/4h dust	-

07/28/2015 **Biocop TF** 6/13

Biocop TFSafety Data Sheet

Copper(I) oxide (1317-39-1)	T	
ATE CLP (oral)	470.000 mg/kg bodyweight	
ATE CLP (vapours)	5.000 mg/l/4h	
ATE CLP (dust,mist)	5.000 mg/l/4h	
Solvent naphtha, petroleum, light aromatic (6474		
LD50 oral rat	8400 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h	
LC50 inhalation rat (ppm)	3400 ppm/4h	
Cumene (98-82-8)		
LD50 oral rat	1400 mg/kg	
LD50 dermal rabbit	12300 μg/kg	
LC50 inhalation rat (ppm)	> 3577 ppm 6 h	
Benzene, 1,2,4-trimethyl- (95-63-6)		
LD50 oral rat	3400 mg/kg	
LD50 dermal rabbit	> 3160 mg/kg	
LC50 inhalation rat (mg/l)	18 g/m³ 4h	
ATE CLP (gases)	4500.000 ppmv/4h	
ATE CLP (vapours)	11.000 mg/l/4h	
ATE CLP (dust,mist)	1.500 mg/l/4h	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
LD50 oral rat	3500 mg/kg	
LD50 dermal rat	> 29.08 mg/kg	
LC50 inhalation rat (mg/l)	29.08 mg/l/4h vapor	
ATE CLP (dermal)	1100.000 mg/kg bodyweight	
ATE CLP (gases)	4500.000 ppmv/4h	
ATE CLP (vapours)	11.000 mg/l/4h	
ATE CLP (dust,mist)	1.500 mg/l/4h	
Ethylbenzene (100-41-4)		
LD50 oral rat	3500 mg/kg	
LD50 dermal rabbit	15400 mg/kg	
LC50 inhalation rat (mg/l)	17.2 mg/l/4h	
ATE CLP (gases)	4500.000 ppmv/4h	
ATE CLP (vapours)	11.000 mg/l/4h	
ATE CLP (dust,mist)	1.500 mg/l/4h	
Rosin (8050-09-7)		
LD50 oral rat	7600 mg/kg	
LD50 dermal rabbit	> 2500 mg/kg	
LC50 inhalation rat (mg/l)	1.5 mg/l/4h	
Toluene (108-88-3)		
LD50 oral rat	636 mg/kg	
LD50 dermal rat	12124 mg/kg	
LD50 dermal rabbit	8390 mg/kg	
LC50 inhalation rat (mg/l)	12.5 mg/l/4h	
LC50 inhalation rat (ppm)	> 26700 ppm/1h	
Benzene (71-43-2)	·	
LD50 oral rat	1800 mg/kg	
LC50 inhalation rat (ppm)	13050 ppm/4h	
Silica, amorphous (7631-86-9)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	> 2.2 mg/l 1h	
Arsenic (7440-38-2)		
LD50 oral rat	15 mg/kg	
ATE CLP (oral)	100.000 mg/kg bodyweight	
ATE CLP (gases)	700.000 ppmv/4h	
ATE CLP (vapours)	3.000 mg/l/4h	
ATE CLP (dust,mist)	0.500 mg/l/4h	
Silica: Crystalline, quartz (14808-60-7)		
LD50 oral rat	500 mg/kg	
	•	

07/28/2015 Biocop TF

Safety Data Sheet

Zinc oxide (1314-13-2)		
LD50 oral rat	> 5000 mg/kg	
Zeolite (1318-02-1)		
LD50 oral rat	5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	2.4 mg/l 1 h	
Zinc pyrithione (13463-41-7)		
LC50 inhalation rat (mg/l)	140 mg/m³ 4 h	

Carcinogenicity data:

Cumene (98-82-8)		
IARC group	2B - Possibly carcinogenic to humans	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
IARC group	3 - Not classifiable	
Ethylbenzene (100-41-4)		
IARC group	2B - Possibly carcinogenic to humans	
Toluene (108-88-3)		
IARC group	3 - Not classifiable	
Benzene (71-43-2)		
IARC group	1 - Carcinogenic to humans	
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens	
Silica, amorphous (7631-86-9)		
IARC group	3 - Not classifiable	
Arsenic (7440-38-2)		
IARC group	1 - Carcinogenic to humans	
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens	
Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)		
IARC group	2B - Possibly carcinogenic to humans	
Silica: Crystalline, quartz (14808-60-7)		
IARC group	1 - Carcinogenic to humans	
Talc (14807-96-6)		
IARC group	3 - Not classifiable	
Zeolite (1318-02-1)		
IARC group	3 - Not classifiable	

Skin corrosion/irritation : Not Applicable,Not classified
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitization : May cause an allergic skin reaction
Germ cell mutagenicity : May cause genetic defects, category 1B.
Carcinogenicity : May cause cancer, category 1A.
Acute Toxicity(Mouth) : Harmful if swallowed
Acute Toxicity(skin) : Not Applicable,Not classified

Reproductive toxicity : Not Applicable, Not classified Specific target organ toxicity (single exposure) : Not Applicable, Not classified Specific target organ toxicity (repeated exposure) : Not Applicable, Not classified

Aspiration hazard : May be fatal if swallowed and enters airways category 1

Symptoms/injuries after inhalation : May be fatal if swallowed and enters airways.

Symptoms/injuries after skin contact : May cause an allergic skin reaction
Symptoms/injuries after eye contact : Causes serious eye damage.
Symptoms/injuries after ingestion : Harmful if swallowed.
Chronic symptoms : May cause cancer.

SECTION 12: Ecological information

12.1. Toxicity

07/28/2015 **Biocop TF** 8/13

Safety Data Sheet

Cuprous oxide (1317-39-1)	
LC50 fishes 1	0.075 mg/l (96 h;danio rerio)
EC50 daphnia 1	0.042 mg/l (48 h; Daphnia similis)
Threshold limit algae 1	0.03 mg/l (96 h; Pseudokirchneriella subcapitata)

Zinc oxide (1314-13-2)	
LC50 fishes 1	1.10 mg/l (96 h; Oncorhynchus mykiss)
EC50 daphnia 1	0.098 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	0.042 mg/l (72 h; Pseudokirchneriella subcapitata)

Zinc pyrithione (13463-41-7)	
LC50 fishes 1	0.0026 mg/l (96 h; Pimephales promelas)
EC50 daphnia 1	0.0082 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	0.028 mg/l (96 h; Selenastrum capricornutum)

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Other adverse effects

PBT/vPvB assessment not available as chemical safety assessment not required/ not conducted An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No

discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be

released into the environment.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

UN-No.(DOT) : 1263 DOT NA no. UN1263

14.2. UN proper shipping name

DOT Proper Shipping Name : PAINT

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable liquid

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III

14.3. Additional information

Transportation by land(ADG Code)

Transport document description : UN 1263 ,PAINT,3,III

07/28/2015 **Biocop TF** 9/13

Safety Data Sheet

Packaging group : III

Hazard Class 3- Flammable liquid

Hazchem Code : 3Y

Class labels (ADR) : 3 - Flammable liquid



Transport by sea

UN-No. (IMDG) : 1263 Packaging Group III

Class (IMDG) : 3- Flammable liquid

EmS-No.(1) : F-E
EmS-No.(2) : S-E
Marine Pollutant Yes

Air transport

UN-No. (IATA) : 1263.

Class (IATA) : 3- Flammable liquid

Packaging group (IATA) : III

DOT Quantity Limitations Passenger aircraft/rail (49 :

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

Other information : No supplementary information available.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed on the United States TSCA (Toxic Substances Control Act) inventory.

Cumene (98-82-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313		
RQ (Reportable quantity, section 304 of EPA's List of Lists):	5000 lb	
SARA Section 313 - Emission Reporting	1 %	
Benzene, 1,2,4-trimethyl- (95-63-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313		
SARA Section 313 - Emission Reporting	1 %	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313		
RQ (Reportable quantity, section 304 of EPA's List of Lists):	100 lb	
SARA Section 313 - Emission Reporting	1 %	
Ethylbenzene (100-41-4)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313		

07/28/2015 **Biocop TF** 10/13

Safety Data Sheet

Cumene (98-82-8)		
RQ (Reportable quantity, section 304 of EPA's List of Lists):	1000 lb	
SARA Section 313 - Emission Reporting	0.1 %	
Toluene (108-88-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313		
Benzene (71-43-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313		
RQ (Reportable quantity, section 304 of EPA's List of Lists):	10 lb (recieved an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule)	
SARA Section 313 - Emission Reporting	0.1 %	
Arsenic (7440-38-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313		
RQ (Reportable quantity, section 304 of EPA's List of Lists):	1 lb (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is $>100~\mu m)$	
SARA Section 313 - Emission Reporting	0.1 %	

15.2. International regulations

CANADA

No additional information available

15.3. US State regulations

California Proposition 65

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

Cumene (98-82-8)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Ethylbenzene (100-41-4)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Toluene (108-88-3)		-		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	
Benzene (71-43-2)		-		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	Yes	
Arsenic (7440-38-2)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	No	
Silica: Crystalline, quartz (14	808-60-7)	•		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

Cumene (98-82-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

07/28/2015 **Biocop TF** 11/13

Safety Data Sheet

Benzene, 1,2,4-trimethyl- (95-63-6)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Xylenes (o-, m-, p- isomers) (1330-20-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Ethylbenzene (100-41-4)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Toluene (108-88-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Benzene (71-43-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Silica, amorphous (7631-86-9)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) List

Arsenic (7440-38-2)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances

Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)

U.S. - Massachusetts - Right To Know List

Silica: Crystalline, quartz (14808-60-7)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

Talc (14807-96-6)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Zinc oxide (1314-13-2)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

15.4. Australian regulations

Poison Schedule (SUSMP): APVMA: 64185

All the constituents of this material are either listed on the Australian Inventory of Chemical Substance(AICS), not required due to AICS:

the nature of the chemical, or have been assessed under the national Industrial Chemicals (Notification and Assessment)

SECTION 16: Other information

: Revision 1.0 – 08/28/2015 - New SDS Created Indication of changes Other information : Mario Garneau, edited by DeGroot Technical Services

07/28/2015 12/13 Biocop TF

Safety Data Sheet

LITERARY REFERENCE: ADG Code - Australian Code for the Transportation of Dangerous Goods by Road and Rail (7th edition)

AICS - Australian Inventory of Chemical Substances

APVMA - Agricultural Pesticides and Veterinary Medicines Australia SUSMP - Standard for the Uniform Scheduling of Medicines & poisons

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material. No warranty, express or implied, is made and New Nautical Coatings, Inc assumes no liability resulting from the use of this SDS. The user must dtermine suitability of this information for his application.

07/28/2015 **Biocop TF** 13/13