

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 03/06/2018 Revision date: 03/06/2018 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : COLORKOTE : liquid Product form Other means of identification : 4900 series

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Antifouling

Details of the supplier of the safety data sheet

New Nautical Coatings, Inc. Sea Hawk Premium Yacht Finishes 14805 49th Street North Clearwater, FL 33762 USA Only: 1-800-528-0997 International: (727) 523-8053

1.4. Emergency telephone number

Emergency number : CHEMTREC day or night inside USA & Canada

1-800-424-9300

:CHEMTREC day or night outside USA & Canada

+1-703-741-5970 :Poison Contro Center 1-800-222-1222

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

H226 Flam. Liq. 3 H302 Acute Tox. 4 Asp. Tox. 1 H304 Aquatic Chronic 1 H410 Aquatic Acute 1 H400 Skin Sens. 1 H317 Carc. 1A H350

Contains 9.5% ingredients of unknown oral toxicity.

2.2. Label elements

GHS-US labeling

Signal word (GHS-US)

Hazard pictograms (GHS-US)



GHS02

GHS07





: Danger : H226 - Flammable liquid and vapor Hazard statements (GHS-US)

H304 - May be fatal if swallowed and enters airways

H302 - Harmful if swallowed

H317 - May cause an allergic skin reaction

H350 - May cause cancer

H400 - Very toxic to aquatic life

H410- Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

03/06/2018 COLORKOTE Page 1

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P261 - Avoid breathing fumes or mist.

P264 - Wash face, hands and forearms thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P272 - Contaminated work clothing must not be allowed out of the workplace

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301+P310 - IF SWALLOWED: Immediately call a doctor.

P301+P312 - If swallowed: Call a doctor if you feel unwell

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P308+P313 - If exposed or concerned: Get medical advice/attention

P321 - Specific treatment (see first aid instructions on this label)

P330 - Rinse mouth

P331 - Do NOT induce vomiting

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use water to extinguish

P391 - Collect spillage

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to licenced waste handling facility.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Sdstance type:

: Multi-constituent

Name	Product identifier	%
Copper Thiocyanate	(CAS No) 1111-67-7	5-15%
Solvent naphtha(petroleum), light aromatic	(CAS No) 64742-95-6	10-25%
Tert-butyl Acetate	(CAS No) 540-88-5	1-5%
Ethylbenzene	(CAS No) 100-41-4	0.01 - 1
Zinc oxide	(CAS No) 1314-13-2	5-10
Tralopyril	(CAS No) 122454-29-9	1-10
Cumene	(CAS No) 98-82-8	0.1-1
Pseudocumene	(CAS No) 95-63-6	5-10
C18-28 Long Chain Chlorinated Paraffins	(CAS No) 63449-39-8	0.1-1
Reaction product of epichlorohydrin and bisphenol A	(CAS No) 25085-99-8	0.1-1
Crystalline silica (quartz)	(CAS No) 14808-60-7	0.1-1
Zinc Omadine	(CAS No) 13463-41-7	1-10

Full text of H-phases: see section 16

3.2. Mixture

Not applicable

03/06/2018 COLORKOTE 2/11

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

41 Description of first aid measures

First-aid measures general Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the

label where possible).

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a First-aid measures after inhalation

POISON CENTER or doctor/physician.

First-aid measures after skin contact IF ON SKIN: Immediately rinse with plenty of water (for at least 15 minutes). Get immediate medical

advice/attention

IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes First-aid measures after eye contact

minimum). Get medical advice/attention.

: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. First-aid measures after ingestion

Most important symptoms and effects, both acute and delayed 4.2.

Symptoms/injuries after inhalation : May cause nose and throat irritation.

Symptoms/injuries after skin contact May cause skin irritation. May cause allecgic skin reaction.

Symptoms/injuries after eye contact : May cause eye irritation. Avoid contact with eyes.

Symptoms/injuries after ingestion : Harmful if swallowed. May cause abdominal pain, nausea, vomiting or drowsiness.

Chronic symptoms : Possible cancer hazard. Contains ingredients which may cause cancer based on animal data.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media : Carbon dioxide. Dry powder. Alcohol-resistant foam. Water spray.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor. May produce carbon oxides under fire conditions.

Explosion hazard : Product is not explosive.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Firefighting instructions Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Do not dispose of fire-fighting water in the environment.

Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-Protection during firefighting

contained breathing apparatus and protective suit (see item 8).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly General measures

equipped with respiratory equipment and full chemical protective gear (see Section 8).

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Wear approved supplied-air

respirator, in case of emergency.

6.2. **Environmental precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

: Exclude sources of ignition and ventilate the area. Soak up spills with inert solids, such as clay or Methods for cleaning up diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the

waste regulations (see Section 13). Waste from this product may be hazardous as defined under RCRA (40 CFR 261).

03/06/2018 COLORKOTE 3/11

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition - No smoking. Use appropriate personal protection equipment (PPE).

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep

container closed when not in use.

Storage temperature

: < 38 °C (100°F)

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure

Ethylbenzene (100-41-4)	
ACGIH TWA (ppm)	20 ppm
OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m³)	545 mg/m³
OSHA PEL (STEL) (ppm)	125 ppm

Zinc oxide (1314-13-2)		
ACGIH TWA (mg/m³)	2 mg/m³	
ACGIH STEL (mg/m³)	10 mg/m ³	
Copper thiocyanate (1111-67-7)		
ACGIH TWA (mg/m³)	0.2 mg/m ³	
ACGIH STEL (ppm)	No Established Limit	
Zinc Omadine(13463-41-7)		
ACGIH TWA mg/m³	0.35 mg/m³	
ACGIH STEL (ppm)	No Established Limit	

Cumene (98-82-8)		
ACGIH TWA (ppm)	50 ppm	
OSHA PEL (TWA) (mg/m³)	245 mg/m³	
OSHA PEL (TWA) (ppm)	50 ppm	
Silica: Crystalline, quartz (14808-60-7)		
ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable fraction)	
OSHA PEL (TWA) (mg/m³)	(10)/(%SiO2 + 2) total dust; (10)/(%SiO2 + 2) respirable fraction	
OSHA PEL (TWA) (ppm)	(250)/(%SiO2 + 5) respirable fraction	
Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)		
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	
Tralopyril (122454-29-9)		
ACGIH TWA (mg/m³)	0.040 mg/m ³	
OSHA PEL (TWA) (mg/m³)	No Established Limit	
OSHA PEL (TWA) (ppm)	No Established Limit	
OSHA PEL (STEL) (mg/m³)	No Established Limit	
OSHA PEL (STEL) (ppm)	No Established Limit	

03/06/2018 COLORKOTE 4/11

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tert-Butyl Acetate (540-88-5)	
ACGIH TWA (ppm)	200 ppm
OSHA PEL (ppm)	200 ppm

8.2. Exposure controls

Appropriate engineering controls : Ensure adequate ventilation, especially in confined areas. Handle with good industrial hygiene and safety.

Personal protective equipment : Face shield. Respiratory protection of the dependent type. Gloves. Protective goggles. Protective clothing.









Hand protection

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.

Eye protection

: Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.

: Wear long sleeves. Handle with gloves

Skin and body protection Respiratory protection

: An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance : liquid.

Color : Blue, Teal, Red, White, Yellow and Black

Odor Codor : Aromatic odour.

Odor Threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : Not Measured Relative evaporation rate (ether=1) : Not Measured Melting point : No data available Freezing point : No data available Boiling point : Not Measured

Flash point : $86.2^{\circ}F(30.1^{\circ}C)$ Self ignition temperature : Na data avilable

Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapor pressure : Not Measured Relative vapor density at 20 °C : Heavier than air

Relative density : 1.35-1.49 g/ml at 25°C (77°F)

Solubility : Water: None Log Pow No data available Log Kow No data available Viscosity, kinematic No data available No data available Viscosity, dynamic Explosive properties : No data available Oxidizing properties No data available No data available Explosive limits

9.2. Other information

No additional information available

03/06/2018 COLORKOTE 5/11

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion:CO and CO2 are formed.Reacts violently with strong oxidizers:increased risk of fire/explosion.reacts with some acids.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremes of tempearture and direct sunlight.

10.5. Incompatible materials

Avoid contact with: Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15354 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
ATE (oral)	3500.000 mg/kg body weight
ATE (dermal)	15354.000 mg/kg body weight
ATE (dust, mist)	1.500 mg/l/4h

Copper thiocyanate (1111-67-7)	
LD50 oral rat	>5000 mg/kg
LD50 skin rabbit	>2000.00 mg/kg Category 4
LD50 inhalation vapor rat	.5.86 mg/l
LD50 inhalation dust/mist_rat	50.00 mg/l/4h Category NA

Tert-Butyl Acatate 540-88-5)		
LD50 oral rat	4500 mg/kg	
LD50 dermal rabbit	2000 mg/kg	
LD50 inhalation rat (mg/l)	12.52 mg/l/4h	
Zinc oxide (1314-13-2)		
LD50 oral rat	5000 mg/kg Category 5	
LD50 skin rabbit	No data available	
LD50 inhalation vapor rat	No data available	
LD50 inhalation dust/mist_mouse	2.50 mg/l/4h Category 4	

Cumene (98-82-8)	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	12300 μg/kg
LC50 inhalation rat (ppm)	> 3577 ppm 6 h
Silica: Crystalline, quartz (14808-60-7)	
LD50 oral rat	500 mg/kg

Carcinogenicity data:

Ethylbenzene (100-41-4)		
IARC group	2B - Possibly carcinogenic to humans	
Cumene (98-82-8)		
IARC group	2B - Possibly carcinogenic to humans	
Toluene (108-88-3)		
IARC group	3 - Not classifiable	
Silica: Crystalline, quartz (14808-60-7)		
IARC group	1 - Carcinogenic to humans	

03/06/2018 COLORKOTE 6/11

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tert-Butyl Acetate (540-88-5)		
IARC group	3 – Not classifiable	
Chlorinated paraffin waxes and hydrocarb	Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)	
IARC group	2B - Possibly carcinogenic to humans	
Tralopyril (122454-29-9)		
LD50 oral rat	28.7 mg/kg Category 4	
LD50 skin rabbit	No data available	
LD50 inhalation vapor rat	>0.08 mg/l,4h	
LD50 inhalation dust/mist mouse	No data available	

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not Applicable, Not classified
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not Applicable, Not classified

Carcinogenicity : May cause cancer
Acute Toxicity(Mouth) Harmful if swallowed.
Acute Toxicity(skin) Not Classified

Reproductive toxicity : Not Applicable, Not classified
Specific target organ toxicity (single exposure) : Not Applicable, Not classified
Specific target organ toxicity (repeated exposure) : Not Applicable, Not classified

Aspiration hazard : May be fatal if swallowed and enters airways

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Other adverse effects

PBT/vPvB assessment not available as chemical safety assessment not required/ not conducted An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No

discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be

released into the environment.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

UN-No.(DOT) : 1263 DOT NA no. UN1263

14.2. UN proper shipping name

DOT Proper Shipping Name : paint

03/06/2018 COLORKOTE 7/11

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III-Minor Danger

14.3. Additional information

Transportation by land(ADR)

Transport document description : UN 1263 ,PAINT,3,III,(D/E)

Packaging group (ADR) : III

Class (ADR) 3- Flammable liquid

State during Transport(ADR-RID) : As liquid

Hazard identification number (Kemler No.) : 30

Clasification code(ADR) : F1

Tunnel restriction code : D/E

Danger labels (ADR) : 3 - Flammable liquid



Transport by sea

UN-No. (IMDG) : 1263 Packaging Group III

Class (IMDG) : 3- Flammable liquid

EmS-No.(1) : F-E EmS-No.(2) : S-E Marine Pollutant Yes

Air transport

UN-No. (IATA) : 1263.

Class (IATA) : 3- Flammable liquid

Packaging group (IATA) : III-Minor Danger

DOT Quantity Limitations Passenger aircraft/rail (49 :

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

Other information : No supplementary information available.

03/06/2018 COLORKOTE 8/11

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed on the United States TSCA (Toxic Substances Control Act) inventory.

Cumene (98-82-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313		
RQ (Reportable quantity, section 304 of EPA's List of Lists):	5000 lb	
SARA Section 313 - Emission Reporting	1 %	
Benzene, 1,2,4-trimethyl- (95-63-6)		
Listed on the United States TSCA (Toxic Substances C Listed on United States SARA Section 313	Control Act) inventory	
SARA Section 313 - Emission Reporting	1 %	
Ethylbenzene (100-41-4)		
Listed on the United States TSCA (Toxic Substances C Listed on United States SARA Section 313	Control Act) inventory	
RQ (Reportable quantity, section 304 of EPA's List of Lists):	1000 lb	
SARA Section 313 - Emission Reporting	0.1 %	
Toluene (108-88-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313		
Benzene (71-43-2)		
Listed on the United States TSCA (Toxic Substances C Listed on United States SARA Section 313	Control Act) inventory	
RQ (Reportable quantity, section 304 of EPA's List of Lists):	10 lb (recieved an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule)	
SARA Section 313 - Emission Reporting	0.1 %	
Tert-Butyl Acetate (540-88-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Section 302(EHS) TPQ	5000 lb	
Section 304- EHS RQ	5000 lb	
ection 313 Listed on US SARA Section 313 1%		

15.2. International regulations

CANADA

No additional information available

15.2.2. National regulations

Ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

Listed on Inventory of Existing Chemical Substances (IECSC)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.

Listed on the Korean ECL (Existing Chemical List) inventory.

Tralopyril (122454-29-9)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on Inventory of Existing Chemical Substances (IECSC)

Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.

Listed on KECI (Chemical Inventory of Korea)

15.3. US State regulations

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

Ethylbenzene (100-41-4)						
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)		
Yes	No	No	No			

03/06/2018 COLORKOTE 9/11

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Cumene (98-82-8)						
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)		
Yes	No	No	No			
Toluene (108-88-3)						
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)		
No	Yes	No	No			
Benzene (71-43-2)			1	1		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)		
Yes	Yes	No	Yes			
Silica: Crystalline, quartz (148	08-60-7)	l	ı			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)		
Yes	No	No	No			

Ethylbenzene (100-41-4)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Cumene (98-82-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Toluene (108-88-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Benzene (71-43-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Silica: Crystalline, quartz (14808-60-7)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)

U.S. - Massachusetts - Right To Know List

Pseudocumene (95-63-6)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

Tralopyril (122454-29-9)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Copper thiocyanate (1111-67-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

03/06/2018 COLORKOTE 10/11

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tralopyril (122454-29-9)

Zinc Omadine(13463-41-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Zinc oxide (1314-13-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

SECTION 16: Other information

Indication of changes : Revision 1.0 - 03/06/2018 - New SDS Created.

Other information : Mario Garneau, edited by MG

NFPA health hazard : 2-intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt medical

attention is given

NFPA fire hazard : 3 – Liquids and solids that can be ignited under almost all

ambient conditions

NFPA reactivity : 0-Normally stable, even under fire exposure conditions, and are

not reactive with water.



HMIS III Rating

Health: 2*Flammability: 3Physical hazard: 0Personal Protection: H

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material. No warranty, express or implied, is made and New Nautical Coatings, Inc assumes no liability resulting from the use of this SDS. The user must dtermine suitability of this information for his application.

03/06/2018 COLORKOTE 11/11