

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Shawkocon
Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

New Nautical Coatings, Inc.
Sea Hawk Premium Yacht Finishes
14805 49th Street North
Clearwater, FL 33762
USA Only: 1-800-528-0997
International: (727) 523-8053

1.4. Emergency telephone numbers

Emergency number : CHEMTREC day or night inside USA & Canada
1-800-424-9300
: CMHETREC day or night outside USA & Canada
+1-703-741-5970
: Poision Control Center
1-800-222-1222

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 3 H226
Muta. 1B H340
Carc. 1B H350
STOT RE 1 H372
Asp. Tox. 1 H304
Aquatic Acute 3 H402
Aquatic Chronic 3 H412

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H340 - May cause genetic defects
H350 - May cause cancer
H372 - Causes damage to organs through prolonged or repeated exposure
H402 - Harmful to aquatic life
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe dust, fume, mist, spray, vapors
P264 - Wash hands, forearms and face thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P273 - Avoid release to the environment
P280 - Wear eye protection, protective gloves, protective clothing
P301+P310 - IF SWALLOWED: Immediately call a doctor
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

Shawkocon

Safety Data Sheet

skin with water/shower
P308+P313 - If exposed or concerned: Get medical advice/attention
P314 - Get medical advice/attention if you feel unwell
P331 - Do NOT induce vomiting
P370+P378 - In case of fire: Use carbon dioxide, dry powder, alcohol resistant foam, or sand to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Stoddard solvent	(CAS No) 8052-41-3	15 - 40
Solvent naphtha, petroleum, light aliphatic	(CAS No) 64742-89-8	10 - 30
Distillates, petroleum, steam-cracked, polymers with light steam-cracked petroleum naphtha	(CAS No) 68410-16-2	7 - 13
Aluminum	(CAS No) 7429-90-5	5 - 10
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	3 - 7
Ethylbenzene	(CAS No) 100-41-4	1 - 5
Naphtha, petroleum, hydrodesulfurized heavy	(CAS No) 64742-82-1	1 - 5
Silica, amorphous	(CAS No) 7631-86-9	1.79
n-Heptane	(CAS No) 142-82-5	0.1 - 1
Octane	(CAS No) 111-65-9	0.1 - 1
Naphthalene	(CAS No) 91-20-3	0.09
Silica: Crystalline, quartz	(CAS No) 14808-60-7	0.016
Benzene	(CAS No) 71-43-2	0.015
Toluene	(CAS No) 108-88-3	0.002

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May be fatal if swallowed and enters airways. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : May cause skin irritation.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

Chronic symptoms : May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

Shawkocon

Safety Data Sheet

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Alcohol-resistant foam. Sand.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.

Explosion hazard : Product is not explosive. Under fire conditions closed containers may rupture or explode.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Scoop solid spill into closing containers or bags. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Exclude sources of ignition and ventilate the area. Waste from this product may be hazardous as defined under RCRA (40 CFR 261).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Containers of this material may be hazardous when emptied. . Do not breathe mist, spray.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Stoddard solvent (8052-41-3)	
ACGIH TWA (ppm)	100 ppm
Remark (ACGIH)	CNS impairment; Eye, skin, and kidney damage; nausea
OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
OSHA PEL (TWA) (ppm)	500 ppm
Distillates, petroleum, steam-cracked, polymers with light steam-cracked petroleum naphtha (68410-16-2)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

Shawkocon

Safety Data Sheet

Naphthalene (91-20-3)	
ACGIH TWA (ppm)	10 ppm
ACGIH STEL (ppm)	15 ppm
Remark (ACGIH)	5 ppm TWA notice of intended changes TLVs
OSHA PEL (TWA) (mg/m ³)	50 mg/m ³
OSHA PEL (TWA) (ppm)	10 ppm
Silica: Crystalline, quartz (14808-60-7)	
ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
OSHA PEL (TWA) (mg/m ³)	(30)/(%SiO ₂ + 2) total dust; (10)/(%SiO ₂ + 2) respirable fraction
OSHA PEL (TWA) (ppm)	(250)/(%SiO ₂ + 5) respirable fraction
Xylenes (o-, m-, p- isomers) (1330-20-7)	
ACGIH TWA (ppm)	100 ppm
ACGIH STEL (ppm)	150 ppm
OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m ³)	655 mg/m ³
OSHA PEL (STEL) (ppm)	150 ppm
Ethylbenzene (100-41-4)	
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment
OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m ³)	545 mg/m ³
OSHA PEL (STEL) (ppm)	125 ppm
Aluminum (7429-90-5)	
ACGIH TWA (mg/m ³)	1 mg/m ³
OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ respirable fraction
Naphtha, petroleum, hydrodesulfurized heavy (64742-82-1)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
n-Heptane (142-82-5)	
ACGIH TWA (ppm)	400 ppm
ACGIH STEL (ppm)	500 ppm (listed under Heptane, all isomers)
OSHA PEL (TWA) (mg/m ³)	2000 mg/m ³
OSHA PEL (TWA) (ppm)	500 ppm
OSHA PEL (STEL) (mg/m ³)	2000 mg/m ³
OSHA PEL (STEL) (ppm)	500 ppm
Octane (111-65-9)	
ACGIH TWA (ppm)	300 ppm
OSHA PEL (TWA) (mg/m ³)	2350 mg/m ³
OSHA PEL (TWA) (ppm)	500 ppm
OSHA PEL (STEL) (mg/m ³)	1800 mg/m ³ Vacated
OSHA PEL (STEL) (ppm)	375 ppm Vacated
Benzene (71-43-2)	
ACGIH TWA (ppm)	0.5 ppm
ACGIH STEL (ppm)	2.5 ppm
OSHA PEL (TWA) (ppm)	1 ppm
OSHA PEL (STEL) (ppm)	5 ppm (see 29 CFR 1910.1028)
OSHA PEL (Ceiling) (ppm)	25 ppm

Shawkocon

Safety Data Sheet

Toluene (108-88-3)	
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	Visual impair; female repro;
Solvent naphtha, petroleum, light aliphatic (64742-89-8)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Silica, amorphous (7631-86-9)	
Remark (ACGIH)	OELs not established
OSHA PEL (TWA) (ppm)	20 mppcf (80)/(% SiO ₂) mg/m ³

8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.



Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. . Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection

: Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Gray.
Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 27.2 °C (81°F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.01 g/cm ³
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

Shawkocon

Safety Data Sheet

Explosive properties : No data available
Oxidizing properties : No data available
Explosion limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremely high or low temperatures. Direct sunlight.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

No data available.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Naphthalene (91-20-3)	
LD50 oral rat	1110 mg/kg
LD50 dermal rabbit	1120 mg/kg
LC50 inhalation rat (mg/l)	> 340 mg/m ³ 1 h
ATE CLP (oral)	500.000 mg/kg body weight
Silica: Crystalline, quartz (14808-60-7)	
LD50 oral rat	500 mg/kg
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (gases)	4500.000 ppmV/4h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
ATE CLP (gases)	4500.000 ppmV/4h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
Naphtha, petroleum, hydrodesulfurized heavy (64742-82-1)	
LD50 oral rat	> 5000 mg/kg (Source: IUCLID)
LD50 dermal rabbit	> 3160 mg/kg (Source: IUCLID)
n-Heptane (142-82-5)	
LD50 oral rat	5000 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	103 g/m ³ 4h
Octane (111-65-9)	
LC50 inhalation rat (mg/l)	118 g/m ³ 4 h
Benzene (71-43-2)	
LD50 dermal rabbit	> 8200 mg/kg
LC50 inhalation rat (mg/l)	44.66 mg/l/4h (vapor)

Shawkocon

Safety Data Sheet

Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h

Solvent naphtha, petroleum, light aliphatic (64742-89-8)	
LD50 oral rat	5000 mg/kg mouse; (Source: IUCLID)
LD50 dermal rabbit	3000 mg/kg (Source: IUCLID)

Silica, amorphous (7631-86-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 2.2 mg/l 1h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Silica: Crystalline, quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

Benzene (71-43-2)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Silica, amorphous (7631-86-9)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: May cause skin irritation.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Chronic symptoms	: May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Shawkocon	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

Shawkocon

Safety Data Sheet

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1263 Paint related material (including paint thinning, drying, removing, or reducing compound), 3, III

UN-No.(DOT) : 1263

DOT NA no. : UN1263

Proper Shipping Name (DOT) : Paint related material including paint thinning, drying, removing, or reducing compound

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Shawkocon

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

Naphthalene	CAS #: 91-20-3
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	100 lb
Section 313	Listed on US SARA Section 313

Xylene (mixed isomers)	CAS #: 1330-20-7
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb

Shawkocon

Safety Data Sheet

CERCLA RQ	100 lb
Section 313	Listed on US SARA Section 313

Ethylbenzene	CAS #: 100-41-4
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	1000 lb
Section 313	Listed on US SARA Section 313

Benzene	CAS #: 71-43-2
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	10 lb
Section 313	Listed on US SARA Section 313

Aluminum (fume or dust)	CAS #: 7429-90-5
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	lb
Section 313	Listed on US SARA Section 313

Toluene	CAS #: 108-88-3
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	1000 lb
Section 313	Listed on US SARA Section 313

15.2. International regulations

CANADA

No additional information available.

15.3. US State regulations

California Proposition 65

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

Naphthalene (91-20-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Silica: Crystalline, quartz (14808-60-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

Shawkocon

Safety Data Sheet

Ethylbenzene (100-41-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Benzene (71-43-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	Yes	
Toluene (108-88-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	
Stoddard solvent (8052-41-3)				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				
Naphthalene (91-20-3)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
Silica: Crystalline, quartz (14808-60-7)				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List				
Xylenes (o-, m-, p- isomers) (1330-20-7)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
Ethylbenzene (100-41-4)				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
Aluminum (7429-90-5)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
n-Heptane (142-82-5)				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				
Octane (111-65-9)				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				
Benzene (71-43-2)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
Toluene (108-88-3)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List				

Shawkocon

Safety Data Sheet


Silica, amorphous (7631-86-9)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revision 4.0: Updated.
Revision date : 06/14/2024
Other information : Author: NMR.

NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard : 1 - Must be preheated before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3*
Flammability : 1
Physical : 0
Personal Protection : Splash goggles, Gloves, Synthetic apron, Vapor respirator

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material.